



Key Features


- SuperClear® technology
- Advanced ergonomic stand for tilt or flat
- HDMI, DisplayPort and VGA inputs
- 50M:1 dynamic contrast ratio
- Supports Windows® 7/8/10 and selected Linux, Chrome, and Android



Product Description

The ViewSonic TD2760 is an ideal solution for both commercial and consumer touch screen applications. With an intuitive 10-point multi-touch display and 1080p Full HD resolution, the 27-inch TD2760 delivers a versatile solution for use in the office or at home, as well as for use as an information kiosk in public areas, retail, and corporate sectors. SuperClear® technology with ultra-wide viewing angles and 50M:1 MEGA Dynamic Contrast Ratio bring greater definition and clarity to multimedia content. For added convenience, cross-platform compatibility works with operating systems such as Windows 10, Linux, Chrome, and Android.* Built-in connectivity options include DisplayPort, HDMI, and VGA ports along with a VESA mount design, offering additional convenience for use as a wall-mounted display. Additionally, the RS232 port provides local control for other RS232 connected devices, while HDMI CEC offers local control of multiple connected devices such as HD set-top boxes, media players, and sound systems. The TD2760's ergonomic stand makes it easy for the user to tilt and raise the monitor, or lay it flat for the most natural position, and create a comfortable working environment. Lastly, low power consumption with Energy Star certification saves energy costs while reducing carbon emission.

*Supports Windows 7/8/10, the latest Linux Kernel 4.X/3.X, the latest Chrome version, and Android 6.0 & 7.0



- | | |
|--|------------------------|
| 1. Internal Speakers | 7. USB Down Stream X 2 |
| 2. VESA Compatible(Wall Mount 100x100mm) | 8. USB Up Stream |
| 3. AC In | 9. RS232 |
| 4. DisplayPort | 10. Earphone |
| 5. HDMI | 11. Audio In |
| 6. VGA | |

Visit Us www.viewsonic.com

DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	VA Technology
Resolution:	1920 x 1080
Resolution Type:	FHD
Static Contrast Ratio:	3,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Colours:	16.7M
Colour Space Support:	8 bit (6 bit + Hi-FRC)
Brightness:	230 cd/m ²
Aspect Ratio:	16:9
Response Time (Typical GTG):	12ms
Response Time (GTG w/OD):	6ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours)::	30000 Hrs (Min)
Curvature::	Flat
Refresh Rate (Hz)::	60
Blue Light Filter::	Yes
Flicker-Free::	Yes
Colour Gamut::	NTSC: 72% size (Typ)
Pixel Size::	0.311 mm (H) x 0.311 mm (V)
Touch Screen::	Projected capacitive, 10-point multi touch
Surface Treatment::	Anti-Glare, Hard Coating (≥6H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 7/8.1/10 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

VGA:	1
USB 3.0 Type A:	2
USB 3.0 Type B:	1
3.5mm Audio In:	1
3.5mm Audio Out:	1
Display Port:	1
Power in:	3-pin Socket (IEC C14 / CEE22)
RS232 In:	1

TOUCH

Touch Technology:	Projected Capacitive
Touch Points:	10
Surface Treatment:	Anti-Glare, Hard Coating (≥6H)
Glasses Thickness:	1.88mm

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	19W
Eco Mode (optimized):	22W
Consumption (typical):	26W
Consumption (max):	28W
Voltage:	AC 100-240V, 50/60 Hz
Stand-by:	0.3W
Power Supply:	Internal

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

CONTROLS

Physical Controls:	1, 2, Up, Down, Power
On Screen Display:	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	15 ~ 90KHz
Frequency Vertical:	50 ~ 76Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
Analog Sync:	Separate/Composite/SOG - RGB Analog

ERGONOMICS

Tilt (Forward/Back):	-4° / 90°
----------------------	-----------

WEIGHT (METRIC)

Net (kg):	7.9
Net Without Stand (kg):	5.5
Gross (kg):	10.2

DIMENSIONS (METRIC) (WXHxD)

Packaging (mm):	753 x 525 x 204
Physical (mm):	660 x 443 x 239
Physical Without Stand (mm):	660 x 410 x 58

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Bronze, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BIS, CCC, China RoHS, China Energy Label
--------------	--

PACKAGE CONTENTS:	TD2760 x1, 3-pin Plug (IEC C13 / CEE22) x1, VGA Cable (Male-Male) x1, HDMI Cable (v1.4; Male-Male) x1, Audio Cable (Male-Male) x1, USB A/B Cable (v3.0; Male-Male) x1, Quick Start Guide x1
-------------------	---

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--