https://www.viewsonic.com/global/products/sheet/VA2409-MHU

ViewSonic MA2409-MHU

Key Features

- SuperClear® IPS panel
- Full HD 1080p resolution
- HDMI, VGA and USBC inputs for flexible connectivity
- Threesided frameless design for seamless viewing
- 75Hz Refresh rate delivers fluid visuals



Product **Description**

The ViewSonic VA2409-MHU is a 24" Full HD monitor featuring HDMI and VGA inputs for business and home use. The optimal screen performance and comfortable viewing without tearing or stuttering is delivered through adaptive sync, eye-care technology, and various ViewMode presets. Simply expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at a low power consumption.





7/21/22, 10:28 AM

https://www.viewsonic.com/global/products/sheet/VA2409-MHU

Л	https://www.view	sonic.com/global/products/sl	heet/VA2409-MHU
DISPLAY		VIDEO INPUT	
Display Size (in.):	24	Digital Sync:	TMDS - HDMI (v1.4), Micro-Packe Type C
Viewable Area (in.):	23.6	Analog Sunai	
Panel Type:	IPS Technology	Analog Sync: ERGONOMICS	Separate - RGB Analog
Resolution:	1920 x 1080	Tilt (Forward/Back):	-3° / 20°
Resolution Type:	FHD (Full HD)	WEIGHT (IMPERIAL)	-3-720-
Static Contrast Ratio:	1,000:1 (typ)	Net (lbs):	6.7
Dynamic Contrast Ratio:	50M:1	Net Without Stand (lbs):	5.8
Light Source:	LED	Gross (lbs):	10.6
Brightness:	250 cd/m² (typ)	WEIGHT (METRIC)	10.0
Colors:	16.7M	Net (kg):	3
Color Space Support:	8 bit (6 bit + FRC)	Net Without Stand (kg):	2.7
Aspect Ratio:	16:9		4.8
Response Time (Typical GTG):	3ms	Gross (kg):	
Viewing Angles:	178º horizontal, 178º vertical	DIMENSIONS (IMPERIAL) (W	23.7 x 16.1 x 4.7
Backlight Life (Hours):	30000 Hrs (Min)	Packaging (in.):	
Curvature:	Flat	Physical (in.):	21 x 16.5 x 7.4
Refresh Rate (Hz):	75	Physical Without Stand (in.):	21 x 12.6 x 2
		DIMENSIONS (METRIC) (WXH	
Adaptive Sync:	Yes	Packaging (mm):	602 x 408 x 120
Blue Light Filter:	Yes	Physical (mm):	534 x 419 x 189
Flicker-Free:	Yes	Physical Without Stand (mm):	534 x 320 x 51
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	GENERAL	
Pixel Size:	0.272 mm (H) x 0.272 mm (V)	Regulations:	RoHS, WEEE
Surface Treatment:	Anti-Glare, Hard Coating (3H)		VA2409-MHU x1, 3-pin Mickey Mo Plug (IEC C5) x1, HDMI Cable (v1 Male-Male) x1, USB Type-C Cable (Male-Male) x1, AC/DC Adapter x1
	Anti-Glare, hard Coating (51)	PACKAGE CONTENTS:	
PC Resolution (max):	1920x1080		Quick Start Guide x1
Mac® Resolution (max):	1920x1080	Recycle/Disposal:	Please dispose of in accordance
PC Operating System:	Windows 10/11 certified; macOS	Warranty:	local, state or federal laws. *Warranty offered may differ from
Mac® Resolution (min):	tested 1920x1080	Wallany.	market to market
CONNECTOR			
VGA:	1		
USB 3.2 Type C DisplayPort Alt mode only :	1		
3.5mm Audio Out:	1		
HDMI 1.4:	1		
Power in:	DC Socket (Center Positive)		
AUDIO			
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	18W		
Eco Mode (optimized):	19W		
Consumption (typical):	22W		
Consumption (max):	87W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	External Power Adaptor		
	External Power Adaptor		
ADDITIONAL HARDWARE			
ADDITIONAL HARDWARE Kensington Lock Slot:	1		
Kensington Lock Slot:			
Kensington Lock Slot: CONTROLS	1 Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual		
Kensington Lock Slot: CONTROLS Physical Controls:	1 Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust,		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display:	1 Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS	1 Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS Temperature:	1 Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C)		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS Temperature: Humidity (non-condensing):	1 Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C)		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS Temperature: Humidity (non-condensing): NALL MOUNT	1 Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C) 20% to 90%		
Kensington Lock Slot: CONTROLS Physical Controls: On Screen Display: DPERATING CONDITIONS Temperature: Humidity (non-condensing): NALL MOUNT VESA Compatible:	1 Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32°F to 104°F (0°C to 40°C) 20% to 90%		

Copyright © ViewSonic Corporation 2000-2022. All rights reserved.