Key **Features**

- SuperClear® IPS technology
- Narrow bezel
- HDMI and VGA inputs
- Dual integrated speakers
- ViewMode technology



Product **Description**

The ViewSonic® VA2710-mh is a Full HD monitor with IPS technology and flexible connectivity for use at home or in the office. With SuperClear® IPS Technology and Full HD resolution, images are clear and detailed from a wide range of viewing angles. The monitor's extensive connectivity options include HDMI and VGA inputs, allowing increased setup flexibility when connecting to other devices. VA2710-mh's narrow bezel design delivers a seamless viewing experience. Built-in dual integrated speakers make this monitor a complete multimedia package. It also comes equipped with Eye Care Technology to help eliminate eye strain caused by extended viewing periods. In addition, ViewSonic's exclusive ViewMode™ function offers a selection of intuitive presets to deliver optimized screen performance for various different applications. With an LED backlight and energy-saving Eco mode, the VA2710-mh is an environmentally friendly display choice.



Visit Us www.viewsonic.com

DISPLAY

DISPLAY	
Monitor Size:	27"W (27" Viewable) LCD monitor
Panel Technology:	IPS Technology, a-si TFT Active Matrix LCD
Resolution:	Full HD 1920 x 1080
Display Area:	597.888mm (H) x 336.312mm (V)
Aspect Ratio:	16:9
Brightness:	300 cd/m ² (Typ)
Contrast Ratio:	1000:1 (Typ)
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angles:	178 degrees / 178 degrees (Typ)
Response Time:	GTG(AVG; Scaler OD) *2: 5ms (Typ)
Backlight:	1 LED light bar
Backlight Life:	30,000 Hrs (Min)
Colours:	16.7M colours (6 bits with Hi-FRC colour depth)
Colour Gamut:	72% (Typ) of NTSC
Panel Surface:	Anti-Glare type, Hard- coating (3H) Haze 25%
INPUT SIGNAL	
Frequency:	Fh = 24 ~ 82KHz ; Fv = 50 ~ 75Hz
Sync:	Separate Sync, TMDS
COMPATIBILITY	
PC:	Windows 7, Windows 8, Windows 8.1, Windows 10 certified
Mac®: CONNECTOR	Power Mac tested
Input:	DB -15 x 1, HDMl x 1 (v1.4 compatible)
Output:	Earphone out x 1 (3.5mm plug)
AUDIO	
Speaker:	2W x 2
POWER	
Power:	3-pin plug (CEE22) x 1
Voltage:	AC 100-240V (Universal); 50/60Hz
ERGONOMICS	
Tilt:	20 ~ -5 degrees
SPECIAL FEATURES	DI II I CIC TI
Eye Care:	Blue light filter, Flicker Free
WALL MOUNT	

OPERATING CONDITIONS

Temperature (° F / ° C): 32° F to 104° F (0°C to 40° C)

Humidity: 20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm): 624.9mm (W) x 435.9mm (H) x 185mm (D)

Physical without stand (mm): 624.9mm (W) x 372.7mm (H) x 50.6mm (D)

Packaging (mm): 682mm (W) x 443mm (H) x 119mm (D)

WEIGHT

Net with stand: 5.0kg (11.0lbs)

Net without stand: 4.0kg (8.8lbs)

Gross: 6.3kg (13.9lbs)

WARRANTY

*Warranty offered may differ from market to market

PACKAGE CONTENTS

LCD Display Power Cable (1.5m) VGA Cable (1.5m)I Audio Cable (1.5m) Quick Start Guide

LCD Display Power Cable (1.5m) VGA Cable (1.5m)I Audio Cable (1.5m) Quick Start Guide

Copyright © ViewSonic Corporation 2000-2021. All rights reserved.

100mm x 100mm

VESA®: