

# ViewSonic® LCD DISPLAY VP2756-2K

## Key Features

- **Lifelike True Beauty:** International color standard Pantone validated and 100% sRGB wide color gamut
- **Precise Color:** ColorPro Verified with pre-factory calibration for overwhelmed Delta E < 2 color accuracy
- **Multimedia Devices:** Support USB-C with 60W high-speed charging, plus HDMI 1.4, DisplayPort 1.2a, USB 3.2
- **Unlimited Flexibility:** Auto Pivot & Ergonomic Stand with tilt, swivel, pivot, and height adjustments
- **The Visible Difference:** 2K QHD(2560\* 1440) resolution IPS panel with 27" frameless design



## Product Description

Designed with creative professionals in mind, the ViewSonic VP2756-2k delivers stunning true-to-life colors on screen. Pantone validated 100% sRGB coverage provides precise color reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

**Visit Us** [www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	20M:1
Light Source:	LED
Brightness:	350 cd/m <sup>2</sup> (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	Adobe RGB: 81% size / 78% coverage (Typ) DCI-P3: 81% size / 81% coverage (Typ) EBU: 108% size / 99% coverage (Typ) REC709: 110% size / 100% coverage (Typ) SMPTE-C: 118% size / 100% coverage (Typ) NTSC: 78% size (Typ) sRGB: 110% size / 100% coverage (Typ)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

**COMPATIBILITY**

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

**CONNECTOR**

USB 3.2 Type A Down Stream:	2
USB 3.2 Type B Up Stream:	1
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1
HDMI 1.4:	1
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

**AUDIO**

Internal Speakers:	2Watts x2
--------------------	-----------

**POWER**

Eco Mode (Conserve):	16.5W
Eco Mode (optimized):	19.3W
Consumption (typical):	22.5W
Consumption (max):	34W
Voltage:	AC 100-240V
Stand-by:	0.3W
Power Supply:	Internal Power Supply

**ADDITIONAL HARDWARE**

Kensington Lock Slot:	1
Cable Organization:	Yes

**CONTROLS**

Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

**WALL MOUNT**

VESA Compatible:	100 x 100 mm
------------------	--------------

**INPUT SIGNAL**

Frequency Horizontal:	15 ~ 130KHz
Frequency Vertical:	24 ~ 75Hz

**VIDEO INPUT**

Digital Sync:	TMD5 - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-Packet - Type C
---------------	---

**ERGONOMICS**

Height Adjust (mm):	130
Swivel:	120°
Tilt (Forward/Back):	-5° / 21°
Pivot (Right/Left):	90° / 90°

**WEIGHT (IMPERIAL)**

Net (lbs):	15.1
Net Without Stand (lbs):	9.8
Gross (lbs):	21

**WEIGHT (METRIC)**

Net (kg):	6.9
Net Without Stand (kg):	4.4
Gross (kg):	9.5

**DIMENSIONS (IMPERIAL) (WXHxD)**

Packaging (in.):	29.1 x 18.3 x 8.9
Physical (in.):	24.1 x 16.15~21.27 x 8.5
Physical Without Stand (in.):	24.1 x 14.3 x 2.1

**DIMENSIONS (METRIC) (WXHxD)**

Packaging (mm):	740 x 465 x 225
Physical (mm):	613 x 410.31~540.31 x 215
Physical Without Stand (mm):	613 x 363 x 53

**GENERAL**

Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI
--------------	--

PACKAGE CONTENTS:	VP2756-2K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
-------------------	---

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--

Power Management:	Energy Star standards, EPEAT
-------------------	------------------------------