

ViewSonic® PROJECTOR PA503XE

Key Features

- 22,000:1 contrast ratio
- SuperColor™ technology
- 5 colour modes
- Auto power off
- Vertical keystone



Product Description

The ViewSonic PA503XE offers impressive visual performance to improve presentations, ideal for use in small business meeting rooms and classrooms. Packed with 4000 ANSI Lumens of brightness and a 22,000:1 contrast ratio, this projector is guaranteed to reproduce the finest of details regardless of the amount of ambient lighting present. ViewSonic exclusive SuperColor™ technology offers a wider range of displayable color for projected images with true-to-life color accuracy. Users can choose from 5 color modes, including standard, brightest, presentation, photo, and movie mode, to select the mode that best suits their needs based on their usage scenario. In addition, the energy-saving SuperEco mode of PA503XE reduces power consumption and extends the lamp life by up to 15,000 hours.



1. Keypad
2. LED indicator
3. Lamp cover
4. Security lock
5. Zoom/Focus
6. Front IR
7. Projection Lens

8. Audio in/out
9. HDMI
10. Dual VGA
11. VGA out
12. Mini USB
13. Video
14. Kensington® Lock Slot

15. RS232

Visit Us  www.viewsonic.com

SPECIFICATION

Native Resolution:	1024x768
DC type:	DC3
Brightness:	4000 ANSI Lumens
Contrast Ratio with SuperEco mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light source life (Nor/SuperEco):	5000/15000
Lamp Watt:	190W
Lens:	F=2.56-2.68, f=22-24.1 mm
Projection Offset:	120%+/-5%
Throw Ratio:	1.96~2.15
Image size:	30" - 300"
Throw Distance:	1.19m-13.11m(100" @3.98m)
Keystone:	±40° (Vertical)
Optical Zoom:	1.1x
Audible Noise (Eco):	27dB
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

INPUT

Computer in (share with component):	2
Composite:	1
Audio-in (3.5mm):	1
HDMI:	1 (Back)

OUTPUT

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	2W

CONTROL

RS232:	1
USB type mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.2kg
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord:	1
VGA cable:	1
Remote Control:	1
QSG & CD:	QSG: 1 / CD: NA

OPTIONAL ACCESSORY

Air Filter:	RSPL
-------------	------