

Key **Features**

- Expansive 32-inch 4K Display
- Utilizes 1152-zone mini-LED backlighting with full-array local dimming
- Rapid 144Hz Refresh Rate
- 3ms (GTG) Response Time
- NVIDIA® G-SYNC® ULTIMATE with NVIDIA®

 Reflex



Product **Description**

Experience a new level of visual performance and upgrade your gameplay on the XG321UG, featuring Mini LED technology that redefines expectations. Engineered with a pixel dense 4K Ultra HD resolution that renders every detail with incredible brightness on our VESA certified DisplayHDR^M 1400 panel. Geared with a rapid 144Hz refresh rate for ultrasmooth gameplay, and a 3ms (GTG) response time to reduce ingame ghosting. Equipped with NVIDIA® G-Sync Ultimate to handle even the most intense action scenes and paired with NVIDIA® Reflex for extreme low latency.

Visit Us

www.viewsonic.com

DISPLAY		CONTROLS	
Display Size (in.):	32	Physical Controls:	Joystick key: Up, Right, Down, Left,
Viewable Area (in.):	32	•	Center; Quick Access; Power
Panel Type:	IPS Technology	On Screen Display:	Game Modes, Display, G-SYNC® Processor, Input Select, Audio Adjust, Setup Menu
Resolution:	3840 x 2160		
Resolution Type:	UHD (Ultra HD)	OPERATING CONDITIONS	22°E to 104°E (0°C to 40°C)
Static Contrast Ratio:	1,000:1 (typ)	Temperature:	32°F to 104°F (0°C to 40°C)
Dynamic Contrast Ratio:	120M:1	Humidity (non-condensing):	20% to 90%
High Dynamic Range:	VESA HDR1400	WALL MOUNT VESA Compatible:	100 x 100 mm
Light Source:	mini LED	INPUT SIGNAL	100 x 100 mm
Brightness:	400; 1400 (w/ HDR Peak (Min))	INFOT SIGNAL	HDMI (v2.0): 30 ~ 150KHz,
Colors:	1.07B	Frequency Horizontal:	DisplayPort (v1.4): 255 ~ 255KHz
Color Space Support:	10 bit true (max; input port and video format)	Frequency Vertical:	HDMI (v2.0): 24 ~ 144Hz, DisplayPort (v1.4): 1 ~ 144Hz
Aspect Ratio:	16:9	VIDEO INPUT	
Response Time (Typical GTG):	3ms	Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4)
Viewing Angles:	178° horizontal, 178° vertical	ERGONOMICS	Dioplay, Cit (VIII)
Backlight Life (Hours):	30000 Hrs (Min)	Height Adjust (mm):	120
Curvature:	Flat	Swivel:	50°
Refresh Rate (Hz):	144	Tilt (Forward/Back):	-5° / 20°
Variable Refresh Rate		WEIGHT (IMPERIAL)	0 7 20
Technology:	G-Sync Ultimate	Net (lbs):	23.8
Blue Light Filter:	Yes	Net Without Stand (lbs):	17.1
Flicker-Free:	Yes	Gross (lbs):	35.1
Color Gamut:	Adobe RGB: 99% coverage (Typ) DCI-P3: 98% coverage (Typ) NTSC: 113% size (Typ) sRGB: 160% size /	WEIGHT (METRIC)	55.1
		Net (kg):	10.8
Divisi Cina	100% coverage (Typ)	Net Without Stand (kg):	7.8
Pixel Size:	0.185 mm (H) x 0.185 mm (V)	Gross (kg):	15.9
Surface Treatment:	Anti-Glare, Hard Coating (3H)	DIMENSIONS (IMPERIAL) (W	
PC Possibility	3840x2160	Packaging (in.):	33.5 x 20.7 x 12.9
PC Resolution (max): Mac® Resolution (max):	3840x2160	Physical (in.):	28.6 x 18.99~23.71 x 10.4
Mace nesolution (max).		Physical Without Stand (in.):	28.6 x 17 x 3.7
PC Operating System:	Windows 10/11 certified; macOS tested	DIMENSIONS (METRIC) (WXHXD)	
Mac® Resolution (min):	3840x2160	Packaging (mm):	850 x 527 x 327
CONNECTOR		Physical (mm):	726 x 482.3~602.3 x 265
USB 3.2 Type A Down Stream:	3	Physical Without Stand (mm):	726 x 432 x 93
USB 3.2 Type B Up Stream:	1	GENERAL	
3.5mm Audio Out:	1		cTUVus, FCC-B, ICES003, CEC,
HDMI 2.0 (with HDCP 2.2):	3	Regulations:	NRCan, REACH, WEEE, RCM, CCC, China RoHS, China Energy Label
DisplayPort:	1		XG321UG x1, 3-pin Plug (IEC C13 /
Power in:	DC Socket (Center Positive)	PACKAGE CONTENTS:	CEE22) x1, HDMI Cable (v2.0; Male- Male) x1, DisplayPort Cable (v1.4; Male-Male) x1, USB A/B Cable (v3.2;
AUDIO			
Internal Speakers:	5Watts x2		Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
POWER		Recycle/Disposal:	Please dispose of in accordance with
Eco Mode (Conserve):	65.2W	,	local, state or federal laws.
Eco Mode (optimized):	71.5W	Warranty:	*Warranty offered may differ from market to market
Consumption (typical):	80.5W		
Consumption (max):	84.5W	-	
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	External Power Adaptor		
***	External Power Adaptor		
Power Supply: ADDITIONAL HARDWARE Kensington Lock Slot:	External Power Adaptor		

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.