

Key Features

- 4,500 ANSI Lumens, offering clear images in any environment
- Up to 300" ultra large screen with lower cost-per-inch
- Easy and flexible connection: dual HDMI ports, USB Type-A port
- Vivid colors with
 ViewSonic's SuperColor™

Technology

 Convenient software updates for projectors via USB connection



Product **Description**

The PA700X is ViewSonic's high brightness XGA business/education projector. With 4,500 ANSI Lumens of high brightness, the projector offers clear images of up-to-300" large screen in meeting rooms, classrooms, or any other bright environment. The dual HDMI ports allow you to flexibly connect to multiple devices, easily switching between content sources. The USB Type-A port can supply power to HDMI wireless dongles, making wireless content streaming more convenient. The projector also allows software updates via USB cable connection with simply your laptops, skipping trips to service centers.





www.viewsonic.com

viewsonic.com/global/products/sheet/PA700X

SPECIFICATION		OTHERS			
Native Resolution:	1024x768	Power Supply	100-240V+/- 10%, 50/60Hz (AC in)		
Brightness:	4500 (ANSI Lumens)	Voltage:			
Contrast Ratio with SuperEco Mode:	12500:1	Power Normal: 295W Consumption: Standby: <0.5W			
Display Color:	1.07 Billion Colors	Operating Temperature: 0~40°C			
Light Source Type:	240W UHP Lamp	Carton: Brown			
Light Source Life (hours) with Normal Mode:	4000	Net Weight:			
Light Source Life (hours) with SuperEco Mode:	12000	Gross 3.80Kg Weight: 3.80Kg			
Lens:	F=2.42-2.53, f=21.85-24.01mm	Dimensions (WxDxH) with	309x234x115mm		
Projection Offset:	115%+/-5%	Adjustment Foot:	3098234811511111		
Throw Ratio:	1.94-2.16	Packing	400x337x168mm		
Optical Zoom:	1.1x	Dimensions:			
Digital Zoom:	0.8x-2.0x	OSD	English, German, French, Swedish, Spanish, Portuguese, Polish, Dutch, T. Chine Finnish, Korean, Russian, Hungarian, Czech, Arabic, Thai, Turkish, Vietnamese, I		
Image Size:	30"-300"	Language: Italian, Total 22		anguages	
Throw Distance:	1.18m-13.17m (100"@3.94m)	User Guide Language:	English, S-Chinese, T-Chinese, Finnish,French,German,Italian,Japanese,Korean,Polish,Portuguese,Russian,Span Total 15 languages		
Keystone:	+/- 40° (V)	STANDARD ACCESSORY			
Audible Noise (Normal):	34dB	Power Cord:		1	
Audible Noise (Eco):	25dB	VGA Cable:		1	
Input Lag:	33.2ms	Remote Control:		1	
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)	QSG:		Yes	
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i,	Air Filter:		Yes (CN Only)	
	1080p	Warranty Card:		Yes (CN Only)	
Video Compatibility:	NTSC, PAL, SECAM	OPTIONAL ACCESSORY			
Horizontal Frequency:	15K-102KHz	Lamp/Light Source:		RLC-128	
Vertical Scan Rate:	23-120Hz	Air Filter:		RSPL	
INPUT		Wall/Ceiling Mount:		PJ-WMK-007	
Computer in (share with component):	1	Carry Bag:		PJ-CASE-008	
HDMI:	2 (HDMI 1.4/ HDCP 1.4)				
Audio-in (3.5mm):	1				
OUTPUT					
Monitor out:	1				
Audio-out (3.5mm):	1				
Speaker:	3W				
USB Type A (Power):	1 (5V/1.5A)				
CONTROL					
RS232 (DB 9-pin male):	1				

USB Type A (Services):

1 (share with USB A Output)

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.