

Key **Features**

- SuperClear® IPS panel
- HDMI, VGA, and USB-C 3.2 inputs for simple connectivity and 65W power delivery
- Super narrow bezel with dual 2.5W speakers
- Ergonomic tilt, swivel, pivot and height adjustment capabilities
- 75Hz Refresh rate delivers fluid visuals



Product **Description**

The ViewSonic VG2709-MHU is a 27" Full HD monitor featuring HDMI, VGA and USB-C inputs for business and home use. Simplify your work with just one cable that provides audio and video, 65W power transfer. The variable refresh rate, eye-care technology, and various ViewMode presets cater for optimal screen performance and comfortable viewing without tearing or stuttering. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at low energy consumption.



Visit Us

www.viewsonic.com

DISPLAY Display Size (in.):	27	WALL MOUNT VESA Compatible:	100 x 100 mm
	27	INPUT SIGNAL	100 X 100 IIIIII
Viewable Area (in.):		Frequency Horizontal:	24 ~ 86KHz
Panel Type:	IPS Technology	Frequency Vertical:	48 ~ 75Hz
Resolution:	1920 x 1080	VIDEO INPUT	40 ~ 75П2
Resolution Type:	FHD (Full HD)	VIDEO INPOT	TMDS - HDMI (v1.4), Micro-Packet
Static Contrast Ratio:	1,000:1 (typ)	Digital Sync:	Type C
Dynamic Contrast Ratio:	50M:1	Analog Sync:	Separate - RGB Analog
Light Source:	LED	ERGONOMICS	
Brightness:	250 cd/m² (typ)	Height Adjust (mm):	130
Colors:	16.7M	Swivel:	360°
Color Space Support:	8 bit true	Tilt (Forward/Back):	-3.5° / 28°
Aspect Ratio:	16:9	Pivot (Right/Left):	90° / 90°
Response Time (Typical GTG):	5ms	WEIGHT (IMPERIAL)	
Response Time (GTG w/OD):	5ms	Net (lbs):	14.8
Viewing Angles:	178° horizontal, 178° vertical	Net Without Stand (lbs):	10.1
Backlight Life (Hours):	30000 Hrs (Min)	Gross (lbs):	19.3
Curvature:	Flat	WEIGHT (METRIC)	
Refresh Rate (Hz):	75	Net (kg):	6.7
Variable Refresh Rate	Yes	Net Without Stand (kg):	4.6
Technology:	res	Gross (kg):	8.7
Blue Light Filter:	Yes	DIMENSIONS (IMPERIAL) (W	
Flicker-Free:	Yes	Packaging (in.):	30.5 x 18.3 x 5.5
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	Physical (in.):	24.2 x 15.03~20.15 x 9.2
Pixel Size:	0.311 mm (H) x 0.311 mm (V)	Physical Without Stand (in.):	24.2 x 14.4 x 2.1
Surface Treatment:		DIMENSIONS (METRIC) (WX	
	Anti-Glare, Hard Coating (3H)	Packaging (mm):	775 x 465 x 140
COMPATIBILITY BC Bosolution (max):	1920x1080	Physical (mm):	614 x 408~538 x 233
PC Resolution (max):		Physical Without Stand (mm):	614 x 366 x 53
Mac® Resolution (max):	1920x1080	GENERAL	014 X 300 X 33
PC Operating System:	Windows 10/11 certified; macOS tested	Regulations:	RoHS, WEEE
Mac® Resolution (min):	1920x1080	riogalationo.	VG2709-MHU x1, 3-pin Plug (IEC
CONNECTOR		PACKAGE CONTENTS:	C13 / CEE22) x1, HDMI Cable (v1.4 Male-Male) x1, USB Type-C Cable
VGA:	1		(Male-Male) x1, Quick Start Guide
USB 3.2 Type C DisplayPort Alt mode only :	1 (65W power charger)	Recycle/Disposal:	Please dispose of in accordance w local, state or federal laws.
3.5mm Audio Out:	1	Warranty:	*Warranty offered may differ from
HDMI 1.4:	1	wantanty.	market to market
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO			
Internal Speakers:	2.5Watts x2		
POWER			
Eco Mode (Conserve):	22W		
Eco Mode (optimized):	26W		
Consumption (typical):	29W		
Consumption (max):	31W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS	100		
Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS	•		
Temperature:	32°F to 104°F (0°C to 40°C)		
	20% to 90%		

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.

Humidity (non-condensing):

20% to 90%