


COLOURS/ DESIGNS



APPLICATIONS

- Ideal for wooden decking, walkways, ramps, steps, boats, swimming pools, entrances, wet areas, outdoor use

FEATURES

- Approx. 8mm thick
- Anti-slip safety mat
- Textured top - highly slip resistant traction in all weather
- Excellent sound absorption
- Heavy duty
- Temperature and water resistant
- Easy installation - screw down
- Dust control properties
- Can be cut to custom lengths
- UV resistant
- Indoor/outdoor use



Drainage



Outdoor Use




Custom Sizes Available



Approx. Thickness

*Guaranteed against failure from manufacturing defects

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	PVC granules & foam	
	Colour	Anthracite	
	Standard Sizes (mm)	See page 2.	
	Surface Finish	PVC granules with holes	
	Backing Finish	PVC foam	
MECHANICAL			
	Slip Resistance	R13 certification	IFA Certification
	Water Displacement	W10 certification	IFA Certification
	Burning Behavior	Bfl-s1	iff certification
	Light Fastness	DIN EN ISO 105-B06:2004-07	SKZ Testing
TEMPERATURE			
	Temperature Range	-25°C to +60°C	
CHEMICAL RESISTANCE			
	Petrol & Oil	○	
	Ozone & Weather	●	
	Flame Resistance	○	
	Animal & Vegetable Oil	○	
	Wear Resistance	●	
	Acid Resistance	○	
	Alkali Resistance	○	
KEY:	● POOR	○ FAIR	● EXCELLENT



THICKNESS (MM)	WIDTH (MM)	ROLL LENGTH (M)	ROLL WEIGHT (KG/M)
8	60	10	1.5
8	90	10	2.2
8	120	10	3.0
8	180	10	4.4

*Sizes vary \pm 2%

