ARMOUR GRIP MATTING

SPEC SHEET



COLOURS/ DESIGNS



APPLICATIONS

Ideal for lining ute decks, vans, trucks, work benches, factory floors

FEATURES

- Approx. 11mm thick
- Multipurpose safety matting on a roll
- Anti-slip textured top
- Heavy duty rubber construction
- Outdoor use







Drainage

Outdoor Use Custom Sizes Available



Approx. Thickness

*Guaranteed against failure from manufacturing defects

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	Natural Rubber	
	Colour	Black	
	Standard Sizes (mm)	See page 2	
	Surface Finish	Raised waffle pattern with holes	
	Backing Finish	Waffle Pattern	
MECHANICAL			
	Hardness	50 Shore A	
	Specific Gravitiy	1.50gm/cm ³	
	Tensile Strength (min)	3 mpa	
TEMPERATURE			
	Temperature Range	-10°C to +70°C	
CHEMICAL RESIST	TANCE		
	Petrol & Oil		
	Ozone & Weather		
	Flame Resistance		
	Animal & Vegetable Oil		
	Wear Resistance		
	Acid Resistance		



ARMOUR GRIP MATTING CONT.

SPEC SHEET



THICKNESS (MM)	WIDTH (MM)	LENGTH (M)	WEIGHT
11	1500	1.5	20kg
11	1500	9m	15kg/m
*Sizes vary ± 2%			

