

### COLOURS/ DESIGNS

- Any logo can be custom printed
- 42 colour options, see page 2.
- Can be PMS colour matched - extra charge may apply

### APPLICATIONS

- Ideal for entrances, high traffic areas, lift doors, reception areas, lobbies hallways/ corridors, floor areas for messages and advertising, indoor use

### FEATURES

- Approx. 8mm thick
- Completely launderable - washable up to 45°C, tumble dry up to 80°C
- Excellent dirt-catching performance
- 30% more absorbent than other mats
- Nylon pile - solution dyed colourfast
- 100% PVC free
- Nitrile rubber backed with non-skid grippers
- Low profile - sits flat without curling
- Slip and trip resistant
- Light resistant and suitable for underfloor heating
- Anti-static



\*Guaranteed against failure from manufacturing defects

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
<b>MATERIAL</b>			
	Polymer	100% nitrile rubber backing and 100% high-twist nylon surface	
	Colours	Custom colours, see page 2 for colour options (Can be PMS colour matched, extra charge may apply)	
	Standard Sizes (mm)	850 x 600 1200 x 850 1450 x 850 1800 x 1200 2400 x 850 Any size available up to 1.8 x 7m	
	Pile Weight	660g	
	Total Weight	2.5kg/m <sup>2</sup>	
	Thickness	8mm	
	Surface Finish	Cut pile carpet	
	Backing Finish	Cleated	
<b>MECHANICAL</b>			
	Colour Fastness	Pass ✓	AATCC 61
	Electostatic Propensity	Pass ✓	AATCC 134
	Surface Flammability	Pass ✓	ASTM D 2859
	High Traction	Pass ✓	NFSI 101-C
<b>TEMPERATURE</b>			
	Temperature Range	Up to +81°C	
<b>CHEMICAL RESISTANCE</b>			
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	
<b>KEY:</b>			
	● POOR	● FAIR	● EXCELLENT



## COLOURS/ DESIGNS

- Any logo can be custom printed
- 42 colour options, see page 2.
- \*Can be PMS colour matched - extra charge may apply\*

## 42 COLOUR OPTIONS:

