INTERLINK MAT SOLID TOP

SPEC SHEET



COLOURS/ DESIGNS



APPLICATIONS

Ideal for in front of machinery, around packing benches, work benches/stations, custom shaped areas

FEATURES

- Approx. 15mm thick
- High quality anti-fatigue properties Smooth surface for easy cleaning

- Ramps eliminate tripping hazard 915 x 915mm modular interlocking system Bevelled edges available in yellow or black
- Indoor use







Anti-Fatigue Inter-Locking Indoor Use



Thickness

^{*}Guaranteed against failure from manufacturing

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	Natural Rubber	
	Colour	Black	
	Standard Sizes (mm)	915 x 915	
	Weight (kg)	8.5	
	Thickness (mm)	Approx. 15mm	
	Surface Finish	Textured	
	Backing Finish	Cleated	
MECHANICAL			
	Hardness	50 Shore A	
	Specific Gravitiy	1.50gm/cm³	
	Tensile Strength (min)	3 mpa	
TEMPERATURE			
	Temperature Range	-10°C to +70°C	
CHEMICAL RESISTANC	CE		
	Petrol & Oil		
	Ozone & Weather		
	Flame Resistance		
	Animal & Vegetable Oil		
	Wear Resistance		
	Acid Resistance		
	Alkali Resistance		

