

INTERLINK MAT WITH HOLES

SPEC SHEET



COLOURS/ DESIGNS



APPLICATIONS

- Ideal for in front of machinery, around packing benches, work benches/stations, wet areas, custom shaped areas

FEATURES

- Approx. 14mm thick
- High quality anti-fatigue properties
- Unique surface texture prevents build-up of dirt
- Drainage holes allow flow of liquids
- 915 x 915mm modular interlocking system
- Bevelled edges available in yellow or black
- Light weight for easy handling
- Indoor use



Anti-Fatigue



Inter-Locking



Drainage



Indoor Use



Approx. Thickness

*Guaranteed against failure from manufacturing defects

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	Natural Rubber	
	Colour	Black	
	Standard Sizes (mm)	915 x 915	
	Weight (kg)	6.5	
	Thickness (mm)	Approx. 14mm	
	Surface Finish	Drainage holes	
	Backing Finish	Cleated	

MECHANICAL			
	Hardness	50 Shore A	
	Specific Gravity	1.50gm/cm ³	
	Tensile Strength (min)	3 mpa	

TEMPERATURE			
	Temperature Range	-10°C to +70°C	

CHEMICAL RESISTANCE			
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	

KEY:



POOR



FAIR



EXCELLENT

