

COLOURS/ DESIGNS



Closed - Solid Top



Open - With Holes

APPLICATIONS

- Ideal for food areas, around machinery, packing areas, wet areas, playgrounds

FEATURES

- Approx. 24mm thick
- Ergonomic and anti-fatigue
- Modular design, interlocking to cover large areas
- Available with and without holes
- Strong and robust
- Edge ramps available to eliminate tripping hazards
- Excellent sound dampening
- Made from recycled material
- UV protected
- Indoor/outdoor use



Anti-Fatigue



ECO



Inter-Locking



Drainage



Outdoor Use



Indoor Use



Approx. Thickness

*Guaranteed against failure from manufacturing defects

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	PVC	
	Colour	Black	
	Standard Sizes (mm)	500 x 500	
	Thickness (mm)	24	
	Weight (kg)	3.50 - Closed 2.78 - Open	
	Surface Finish	Textured solid top (Closed), Textured with holes (Open)	
	Backing Finish	Cleated	
MECHANICAL			
	Hardness	78 Shore	
	ADA Compliance	Yes	
	Co-Efficient of Friction	Wet - 34-35 Dry - 90-92	
	Fire Exposure	Passed	
	UV Stabilised	Yes	
TEMPERATURE			
	Temperature Range	-30°C to +60°C	
CHEMICAL RESISTANCE			
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	

KEY:



POOR



FAIR



EXCELLENT

