

COLOURS/ DESIGNS



Black

APPLICATIONS

- Ideal for bridge bearings, elastomeric bearing pad, packers under bridges, car engine/body mount

FEATURES

- Approx. 12.7mm or 25mm thick
- Natural rubber
- Outdoor use



Outdoor Use



Approx. Thickness



Approx. Thickness

*Guaranteed against failure from manufacturing defects

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	Natural Rubber	
	Colour	Black	
	Standard Sizes (mm)	1200mm wide x 10m	
	Weight (kg)	108 and 330	
	Thickness (mm)	12.7 and 25	
	Insertion Material	-	
	Surface Finish	Smooth	
	Backing Finish	Smooth	
MECHANICAL			
	Hardness	IRHD60	
	Specific Gravity	1.10 ± 0.05	
	Tensile Strength (min)	17	BS903: PTA6
	Elongation (min)	500%	BS903: PTA6
	Compression set after 30min at 70°C	30%	BS903: PTA6
TEMPERATURE			
	Temperature Range	-30°C to + 70°C	
CHEMICAL RESISTANCE			
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	
PACKAGING			
	Rolled on cardboard tube Ø 80mm. Wrapped in black polyethylene film.		
KEY:			
	● POOR	● FAIR	● EXCELLENT

