

PROFLEX INSERTION PLUS

SPEC SHEET



COLOURS/ DESIGNS



Black

APPLICATIONS

- Ideal for conveyors, gasket sealing, workbenches, van/ute liner

FEATURES

- Available in six thicknesses
- 2-ply cotton insertion
- Hard wearing - very durable
- Absorbs noise
- Can be cut to custom lengths
- Tear resistance
- Indoor/outdoor use



Outdoor Use



Custom Sizes Available



Approx. Thickness

*Guaranteed against failure from manufacturing defects

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	Natural Rubber	
	Colour	Black	
	Insertion Material	Cotton 2 ply	
	Surface Finish	Smooth	
	Surface Finish	Smooth	
MECHANICAL			
	Hardness	60 Shore A	ASTM D 2240
	Specific Gravity	1.6gm/cm ³	ASTM D 297
	Tensile Strength (min)	40kg/mpa	ASTM D 412
	Elongation (min)	200%	ASTM D 412
TEMPERATURE			
	Temperature Range	-30°C to + 70°C	
CHEMICAL RESISTANCE			
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	
PACKAGING			
	Rolled on cardboard tube Ø 80mm. Wrapped in black polyethylene film.		
KEY:			
	● POOR	● FAIR	● EXCELLENT



PROFLEX INSERTION PLUS CONT.

SPEC SHEET



THICKNESS (MM)	WIDTH (MM)	ROLL LENGTH (M)	ROLL WEIGHT (KG)
3	25	10	1
3	50	10	2
3	75	10	3
3	100	10	4.2
3	150	10	6.3
3	200	10	8.3
3	300	10	12.5
3	1200	10	50
6	25	10	2.3
6	50	10	4.6
6	75	10	6.9
6	100	10	9.2
6	150	10	13.8
6	200	10	18.3
6	300	10	27.5
6	1200	10	110
8	25	5	1.5
8	50	5	3.0
8	75	5	4.5
8	100	5	6.1
8	150	5	9.1
8	200	5	12.1
8	300	5	46.2
8	1200	5	73
10	25	5	1.9
10	50	5	3.8
10	75	5	5.6
10	100	5	7.5
10	150	5	11.3
10	200	5	15
10	300	5	22.6
10	1200	5	91
12	25	5	2.3
12	50	5	4.5
12	75	5	6.8
12	100	5	9
12	150	5	13.5
12	200	5	18
12	300	5	27
12	1200	5	108

*Sizes vary ± 2%

