ALFRESCO OUTDOOR CARPET

PROPERTIES

MATERIAL

MEASURED CHARACTERISTICS

Polymer

Colour

Thickness

Pile Weight

Total Weight

Surface Finish

Standard Sizes (mm)

VALUE

Charcoal

6mm

600g/m2

780g/m2

Needlepunch

Polypropylene surface with a resin backing

2000mm wide x 25m

4000mm wide x 25m



STANDARD

ISO 1765

ISO 8543

COLOURS/ DESIGNS



APPLICATIONS

Ideal for patios, ramps, boats, garages, wooden decking, entrances, schools, wet areas

FEATURES

- Approx. 6mm thick UV stabilised
- Polypropylene top Resin backing
- Can be glued down or screwed down to secure
- Indoor/outdoor use



Custom Sizes Outdoor Use Available



Ç	1	

è	Indoor Use	

	Backing Finish	Resin			
MECHANICAL					
	UV Stabilised	Yes			
	Burning Behavior	Efl rating	EN1305-1		
	Anti Static	Yes			
	Anti Slip	Yes - DS rating			
TEMPERATURE					
	Temperature Range				
CHEMICAL RESISTANCE					
	Petrol & Oil				
	Ozone & Weather				
	Flame Resistance				
	Animal & Vegetable Oil				
	Wear Resistance				
	Acid Resistance				
	Alkali Resistance				
KEY:	POOR FAIR	EXCELLENT			

