


## COLOURS/ DESIGNS



Blue



Grey



Black

## APPLICATIONS

- Ideal for wet factory areas, swimming pools, boats, showers, marine environments, food manufacturing environments

## FEATURES

- Approx. 12mm thick
- Excellent anti-fatigue qualities
- Very durable tubular construction
- Impervious to water, oils, greases and acids
- Flame and chemical resistant
- Manufactured from non-toxic food grade PVC
- Soft and flexible
- 100% recyclable
- Can be cut to custom lengths
- Easy to clean, hose down
- UV protected



Anti-Fatigue



Drainage



Outdoor Use



Custom Sizes Available



Approx. Thickness

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
<b>MATERIAL</b>			
	Polymer	PVC	
	Colour	Blue, Grey, Black	
	Standard Sizes (mm)	See page 2.	
	Surface Finish	Tubular	
	Backing Finish	Tubular	
<b>MECHANICAL</b>			
	Burning Behavior	Resistant	DIN4102 Part 1
<b>TEMPERATURE</b>			
	Temperature Range	-12°C to +60°C	
	Melt Temperature	150°C	At 1500psi
<b>CHEMICAL RESISTANCE</b>			
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	
<b>KEY:</b>	● POOR	● FAIR	● EXCELLENT

\*Aqua Tube Matting can be cleaned in an autoclave but it needs to be sufficiently cooled before handling as it will be extremely soft. Please note the melt temperature above. An autoclave sterilises and cleans the matting if required when it's put in to food manufacturing environments.

