LINK MAT

SPEC SHEET



COLOURS/ DESIGNS



APPLICATIONS

Ideal for in front of machinery, around packing benches

FEATURES

- Slip resistant checker-plate finish
- Very cost effective
- Bevelled edges to eliminate tripping Easy removal for cleaning
- Interlocks for longer lengths when required
- Indoor use







Anti-Fatigue Inter-Locking

Approx. Thickness

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	Natural Rubber	
	Colour	Black	
	Standard Sizes (mm)	915 x 915	
	Weight (kg)	6.5	
	Thickness (mm)	Approx. 14mm	
	Surface Finish	Drainage holes	
	Backing Finish	Cleated	
MECHANICAL			
	Hardness	55 Shore A	
	Specific Gravitiy	1.50gm/cm ³	
	Tensile Strength (min)	3 mpa	
TEMPERATURE			
	Temperature Range	-30°C to +70°C	
CHEMICAL RESISTA	NCE		
	Petrol & Oil		
	Ozone & Weather		
	Flame Resistance		
	Animal & Vegetable Oil		
	Wear Resistance		
	Acid Resistance		
	Alkali Resistance		
KEY:	POOR FAIR	EXCELLENT	

