NORDIC MARINE CARPET

SPEC SHEET



COLOURS/ DESIGNS





Charcoal

APPLICATIONS

Ideal for decks, ramps, boats, kindergartons

FEATURES

- Approx. 9mm thick UV stabilised

- Can be cut to custom lengths Dual rib polypropylene surface Resin backing Indoor/outdoor use







Custom Sizes Outdoor Use Available

Indoor Use



Approx. Thickness

valiable		
+		
mm		

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD	
MATERIAL				
	Polymer	Polypropylene surface with a resin backing		
	Colour	Charcoal, Grey		
	Standard Sizes (mm)	2000 x 30m		
	Thickness	9mm	ISO 1765	
	Pile Weight	900g/m2		
	Total Weight	1150g/m2	ISO 8543	
	Surface Finish	Needlepunch rib		
	Backing Finish	Resin		
MECHANICAL				
	UV Stabilised	Yes		
	Flammability	Efl rating	EN 13501-1	
	Slip Resistance	Yes - DS rating		
TEMPERATURE				
	Temperature Range			
CHEMICAL RESISTANCE				
	Petrol & Oil			
	Ozone & Weather			
	Flame Resistance			
	Animal & Vegetable Oil			
	Wear Resistance			
	Acid Resistance			
	Alkali Resistance			
KEY:	POOR FAIR	EXCELLENT		

