NORDIC MARINE CARPET RUNNER

SPEC SHEET



COLOURS/ DESIGNS





Charcoal

APPLICATIONS

Ideal for decks, ramps, boats, entrance ways

FEATURES

- Approx. 9mm thick
- UV stabilised Can be cut to custom lengths
- Dual rib polypropylene surface Gel Foam backing
- Indoor/outdoor use







Available

Custom Sizes Outdoor Use

Indoor Use



Thickness

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	100% polypropylene surface with a gel foam backing	
	Colour	Charcoal, Grey	
	Standard Sizes (mm)	1000 x 30m	
	Thickness	9mm	ISO 1765
	Pile Weight	900g/m2	
	Total Weight	1500g/m2	ISO 8543
	Surface Finish	Needlepunch rib	
	Backing Finish	Gel Foam	
MECHANICAL			
	UV Stabilised	Yes	
	Flammability	Efl rating	EN 13501-1
	Slip Resistance	Yes - DS rating	
TEMPERATURE			
	Temperature Range		
CHEMICAL RESIS	STANCE		
	Petrol & Oil		
	Ozone & Weather		
	Flame Resistance		
	Animal & Vegetable Oil		
	Wear Resistance		
	Acid Resistance		
	Alkali Resistance		
KEY:	POOR FAIR	EXCELLENT	

