


O RING MAT

SPEC SHEET



COLOURS/ DESIGNS



Black

APPLICATIONS

- Ideal for walkways, commercial warehouses, playgrounds, entrances

FEATURES

- Approx. 16mm thick
- Heavy duty anti-fatigue
- Absorbs shock and noise
- Holes for drainage in wet areas
- All edges bevelled for safety
- Can be made to any size using connectors
- Indoor/outdoor use



Anti-Fatigue



Drainage



Outdoor Use



Indoor Use



Custom Sizes Available



Approx. Thickness

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	Natural Rubber	
	Colour	Black	
	Standard Sizes (mm)	1000 x 500 1200 x 800 1500 x 1000	
	Thickness	16mm	
	Surface Finish	Drainage Holes	
	Backing Finish	Cleated	
MECHANICAL			
	Hardness	55 Shore A	
	Specific Gravity	1.50gm/cm ³	
	Tensile Strength (min)	3 mpa	
TEMPERATURE			
	Temperature Range	-30°C to +70°C	
CHEMICAL RESISTANCE			
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	
KEY:	● POOR	● FAIR	● EXCELLENT

