

COLOURS/ DESIGNS



Black

APPLICATIONS

- Ideal for anti-vibration on workbenches, welding areas, chillers, automotive, gaskets, seals & marine, high temperatures

FEATURES

- Excellent resistance to ozone & weather - UV stabilised
- Flame resistant
- Can be cut to custom lengths
- Available in four thicknesses
- Indoor/outdoor use



Outdoor Use



Custom Sizes Available



Approx. Thickness

PROPERTIES	MEASURED CHARACTERISTICS	VALUE	STANDARD
MATERIAL			
	Polymer	Neoprene Rubber	
	Colour	Black	
	Insertion Material	-	
	Surface Finish	Smooth	
	Backing Finish	Smooth	
MECHANICAL			
	Hardness	60 Shore A	ASTM D 2240
	Density	1.5gm/cm ³	ASTM D 297
	Tensile Strength (min)	9 MPa	ASTM D 412
	Elongation (min)	350%	ASTM D 412
	Compression set after 24h at 70°C	50%	ASTM D395
TEMPERATURE			
	Temperature Range	-30°C to + 80°C	
CHEMICAL RESISTANCE			ASTM D 1149
	Petrol & Oil	●	
	Ozone & Weather	●	
	Flame Resistance	●	
	Animal & Vegetable Oil	●	
	Wear Resistance	●	
	Acid Resistance	●	
	Alkali Resistance	●	
PACKAGING			
Rolled on cardboard tube Ø 80mm. Wrapped in black polyethylene film.			
KEY:			
	● POOR	● FAIR	● EXCELLENT



THICKNESS (MM)	WIDTH (MM)	ROLL LENGTH (M)	ROLL WEIGHT (KG)
1.5	25	10	0.6
1.5	50	10	1.2
1.5	75	10	1.7
1.5	100	10	2.3
1.5	150	10	3.5
1.5	200	10	4.5
1.5	300	10	7
1.5	1200	10	28
3	25	10	1.2
3	50	10	2.4
3	75	10	3.5
3	100	10	4.8
3	150	10	7
3	200	10	9.5
3	300	10	14.3
3	1200	10	57
4.5	25	10	1.8
4.5	50	10	3.6
4.5	75	10	5.4
4.5	100	10	7
4.5	150	10	10.7
4.5	200	10	14.3
4.5	300	10	21.4
4.5	1200	10	86
6	25	10	2.4
6	50	10	4.8
6	75	10	7.2
6	100	10	9.6
6	150	10	14.4
6	200	10	19.2
6	300	10	28.8
6	1200	10	115

*Sizes vary ± 2%

