

# Backed Needlepunch Carpet

## BPIR Declaration

Version: v1

---

### Designated building product: Class 1

---

### Declaration

Arrow Matting Systems Ltd has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

---

### Product/system

Name	Backed Needlepunch Carpet
Line	Needlepunch carpet with a gel-foam backing.
Identifier	EVE2MR-CHR, TEC2MR-CHR/GRY/BLU

---

### Description

Backed Needlepunch Carpet is manufactured from polypropylene yarn with a gel-foam backing. It is an interior floor covering. It comes in charcoal/grey/blue. The carpet is intended for being loose laid as a temporary flooring solution, however can be glued down in accordance with our install guides.

It comes in 2m wide with an approx thickness of 3-5mm.

---

### Scope of use

Backed Needlepunch Carpet: • Is suitable for use as a temporary interior floor covering. • Is suitable for light traffic areas. • Is not suitable for outdoor use or areas exposed to sunlight • Is not suitable for use where the floor covering is exposed in interior areas of building where there are building code obligations under C3.4(b). Protection to fire Efl (EN14041) • Is not suitable for use in interior wet areas, i.e. on floors adjacent to sanitary fixtures or sanitary appliances, for E3 Internal Moisture control, i.e. leakage. (Note: this is not a reference to slip resistance) • Is not suitable for use on floors in food preparation areas (including residential/domestic kitchens) •

Is not suitable for use on floors between adjoining tenancies, in conjunction with other acoustic measures • Is not suitable for use in buildings with adjoining vertical tenancies in conjunction with other acoustic measures

---

## Conditions of use

Backed Needlepunch Carpet: • Must be maintained according to Needlepunch Carpet Maintenance Guide.

---

## Relevant building code clauses

**B2 Durability – B2.3.1 (c)**

**F2 Hazardous building materials – F2.3.1**

---

## Contributions to compliance

B2: Backed Needlepunch Carpet has a durability of 2 years where loose laid & 5 years when installed & maintained according to the guidelines. Refer to the design and installation requirements for further information.

F2: Backed Needlepunch Carpet is safe when handled. There are no requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3, 2017.

---

## Supporting documentation

The following additional documentation supports the above statements:

**Needlepunch Carpet  
Cleaning Instructions**

v1

[https://cdn.shopify.com/s/files/1/0601/7243/5681/files/NeedlePunch\\_Carpet\\_Cleaning\\_Guide.pdf?v=1701206394](https://cdn.shopify.com/s/files/1/0601/7243/5681/files/NeedlePunch_Carpet_Cleaning_Guide.pdf?v=1701206394)

<b>Needlepunch Carpet Installation Guide</b>	v1	<a href="https://cdn.shopify.com/s/files/1/0601/7243/5681/files/AMS_Installation_Guides_Needlepunch_Carpet_s.pdf?v=1701208254">https://cdn.shopify.com/s/files/1/0601/7243/5681/files/AMS_Installation_Guides_Needlepunch_Carpet_s.pdf?v=1701208254</a>
--	----	---

For further information supporting Backed Needlepunch Carpet claims refer to our website.

---

## Contact details

<b>Manufacture location</b>	Overseas
<b>Legal and trading name of manufacturer</b>	Condor Group T/A Vebe Floorcoverings
<b>Legal and trading name of importer</b>	Arrow Matting Systems Ltd
<b>Importer address for service</b>	1D Quadrant Dr Lower Hutt 5010
<b>Importer website</b>	<a href="http://www.amsdistributors.co.nz">www.amsdistributors.co.nz</a>
<b>Importer NZBN</b>	9429035794905
<b>Importer email</b>	sales@amsdistributors.co.nz
<b>Importer phone number</b>	0800 806 287

---

## Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Backed Needlepunch Carpet is not subject to a warning or ban under [s26 of the Building Act](#).

Signed for and on behalf of **Arrow Matting Systems Ltd**:



Logan Hart  
General Manager  
Oct 2023

---

**ARROW MATTING SYSTEMS LTD**  
1D Quadrant Dr Lower Hutt 5010 New Zealand  
0800 806 287 | [www.amsdistributors.co.nz](http://www.amsdistributors.co.nz)

# Appendix

Note: The below appendix includes information relating to BPIR Ready.

Publishing this information is not a requirement under BPIR. Its inclusion here is to provide a reference for how this BPIR summary was generated as well as to help summary creators understand the performance clauses suggested by BPIR Ready.

## BPIR Ready selections

Category: Floor coverings

	Yes	No
Use on access routes		x
Use in areas with floor surface fire obligations		x
Use in wet areas		x
Use in food preparation areas		x
Part of a system for acoustic performance		x

## Building code performance clauses

### B2 Durability

B2.3.1

*Building elements* must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (c) 5 years if: the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and failure of those building elements to comply with the building code would be easily detected during normal use of the building.

## F2 Hazardous building materials

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction of buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.