

PROFLEX[®] INSERTION 1-PLY



Proflex Insertion is a natural rubber sheet, reinforced with cotton fabric for improved tear resistance and dimensional stability. It has good physical properties such as mechanical strength and tear strength and has moderate abrasion resistance making it suitable for general insulating or isolating and general gasket sealing applications.

Proflex rubber comes in a 10m roll, or can be cut to any length. A cutting fee will apply to any cut length.









FEATURES

- Ideal for ute/van liner, mud guards, conveyors, protection
- 1-ply cotton insertion
- Hard wearing - very durable
- Absorbs noise
- Tear resistance
- Can be cut to custom lengths
- Available in four thicknesses
- Indoor/outdoor use*

*Can be used outdoor but may be affected by ozone over time



PROFLEX[®] INSERTION 1-PLY CONT.

	CODE (CUSTOM LENGTH PER M)	THICKNESS (MM)	WIDTH (MM)
25MM WIDE 	ISR1.5/25W	1.5	25
	ISR3/25W	3	25
	ISR4.5/25W	4.5	25
	ISR6/25W	6	25
50MM WIDE 	ISR1.5/50W	1.5	50
	ISR3/50W	3	50
	ISR4.5/50W	4.5	50
	ISR6/50W	6	50
75MM WIDE 	ISR1.5/75W	1.5	75
	ISR3/75W	3	75
	ISR4.5/75W	4.5	75
	ISR6/75W	6	75
100MM WIDE 	ISR1.5/100W	1.5	100
	ISR3/100W	3	100
	ISR4.5/100W	4.5	100
	ISR6/100W	6	100
150MM WIDE 	ISR1.5/150W	1.5	150
	ISR3/150W	3	150
	ISR4.5/150W	4.5	150
	ISR6/150W	6	150
200MM WIDE 	ISR1.5/200W	1.5	200
	ISR3/200W	3	200
	ISR4.5/200W	4.5	200
	ISR6/200W	6	200
300MM WIDE 	ISR1.5/300W	1.5	300
	ISR3/300W	3	300
	ISR4.5/300W	4.5	300
	ISR6/300W	6	300
1200MM WIDE 	ISR15W	1.5	1200
	ISR30W	3	1200
	ISR45W	4.5	1200
	ISR60W	6	1200

*Mat sizes may vary + / - 5%. All rolls are 10m long. A cutting fee applies to any cut length less than 10m.