

PROFLEX^X INSERTION PLUS 2-PLY



Heavy duty, natural rubber sheet, reinforced with a 2ply cotton fabric for improved tear resistance and dimensional stability. Has good physical properties such as mechanical strength and tear strength and has moderate abrasion resistance, making it suitable for general insulating or isolating and gasket sealing applications.

Proflex rubber 3mm-6mm comes in a 10m roll, Proflex rubber 8mm-12mm comes in a 5m roll. They can be cut to any length, however a cutting fee will apply.



FEATURES

- Ideal for conveyors, gasket sealing, workbenches, van/ute liner, protection
- 2-ply cotton insertion
- Hard wearing - very durable
- Absorbs noise
- Tear resistance
- Can be cut to custom lengths
- Available in six thicknesses
- Indoor/outdoor use*

*Can be used outdoor but may be affected by ozone over time



PROFLEX[®] INSERTION PLUS 2-PLY CONT.

	CODE (CUSTOM LENGTH PER M)	THICKNESS (MM)	WIDTH (MM)
25MM WIDE 	ISRP3/25W	3	25
	ISRP4.5/25W	4.5	25
	ISRP6/25W	6	25
	ISRP8/25W	8	25
	ISRP10/25W	10	25
	ISRP12/25W	12	25
50MM WIDE 	ISRP3/50W	3	50
	ISRP4.5/50W	4.5	50
	ISRP6/50W	6	50
	ISRP8/50W	8	50
	ISRP10/50W	10	50
	ISRP12/50W	12	50
75MM WIDE 	ISRP3/75W	3	75
	ISRP4.5/75W	4.5	75
	ISRP6/75W	6	75
	ISRP8/75W	8	75
	ISRP10/75W	10	75
	ISRP12/75W	12	75
100MM WIDE 	ISRP3/100W	3	100
	ISRP4.5/100W	4.5	100
	ISRP6/100W	6	100
	ISRP8/100W	8	100
	ISRP10/100W	10	100
	ISRP12/100W	12	100
150MM WIDE 	ISRP3/150W	3	150
	ISRP4.5/150W	4.5	150
	ISRP6/150W	6	150
	ISRP8/150W	8	150
	ISRP10/150W	10	150
	ISRP12/150W	12	150
200MM WIDE 	ISRP3/200W	3	200
	ISRP4.5/200W	4.5	200
	ISRP6/200W	6	200
	ISRP8/200W	8	200
	ISRP10/200W	10	200
	ISRP12/200W	12	200
300MM WIDE 	ISRP3/300W	3	300
	ISRP4.5/300W	4.5	300
	ISRP6/300W	6	300
	ISRP8/300W	8	300
	ISRP10/300W	10	300
	ISRP12/300W	12	300
1200MM WIDE 	ISRP30W	3	1200
	ISRP45W	4.5	1200
	ISRP60W	6	1200
	ISRP80W	8	1200
	ISRP100W	10	1200
	ISRP120W	12	1200

*Mat sizes may vary + / - 5%. 3-6mm thick rolls are 10m long, 8-12mm thick rolls are 5m long. A cutting fee applies to any cut length less than full roll size.