

PROFLEX COMMERCIAL NEOPRENE



Commercial grade, abrasion and impact resistant, neoprene rubber sheet. It has excellent mechanical strength, is flexible and resilient with high temperature and flame resistance. Commercial Neoprene Rubber is most suitable for sealing, bearing or isolating applications and anti-vibration where these are present.

Proflex rubber comes in a 10m roll, or can be cut to any length. A cutting fee will apply to any cut length.

FEATURES

- Ideal for anti-vibration on workbenches, welding areas, chillers, automotive, gaskets, seals & marine, high temperatures
- Excellent resistance to ozone & weather - UV stabilised
- Flame resistant
- Can be cut to custom lengths
- Available in four thicknesses
- Indoor/outdoor use



PROFLEX PREMIUM NEOPRENE CONT.

	CODE (CUSTOM LENGTH PER M)	THICKNESS (MM)	WIDTH (MM)
25MM WIDE 	CR1.5/25W	1.5	25
	CR3/25W	3	25
	CR4.5/25W	4.5	25
	CR6/25W	6	25
50MM WIDE 	CR1.5/50W	1.5	50
	CR3/50W	3	50
	CR4.5/50W	4.5	50
	CR6/50W	6	50
75MM WIDE 	CR1.5/75W	1.5	75
	CR3/75W	3	75
	CR4.5/75W	4.5	75
	CR6/75W	6	75
100MM WIDE 	CR1.5/100W	1.5	100
	CR3/100W	3	100
	CR4.5/100W	4.5	100
	CR6/100W	6	100
150MM WIDE 	CR1.5/150W	1.5	150
	CR3/150W	3	150
	CR4.5/150W	4.5	150
	CR6/150W	6	150
200MM WIDE 	CR1.5/200W	1.5	200
	CR3/200W	3	200
	CR4.5/200W	4.5	200
	CR6/200W	6	200
300MM WIDE 	CR1.5/300W	1.5	300
	CR3/300W	3	300
	CR4.5/300W	4.5	300
	CR6/300W	6	300
1200MM WIDE 	CR15W	1.5	1200
	CR30W	3	1200
	CR45W	4.5	1200
	CR60W	6	1200

*Mat sizes may vary + / - 5%. All rolls are 10m long. A cutting fee applies to any cut length less than 10m.