

PROFLEX PREMIUM NEOPRENE



Premium grade, abrasion and impact resistant, neoprene rubber sheet. It has excellent mechanical strength, is flexible and resilient with high temperature and flame resistance. Premium Neoprene Rubber is most suitable for sealing, bearing or isolating applications and anti-vibration where these are present.




Proflex rubber comes in a 10m roll, or can be cut to any length. A cutting fee will apply to any cut length.

FEATURES

- Ideal for anti-vibration on workbenches, welding areas, chillers, automotive, gaskets, seals & marine, high temperatures
- Excellent resistance to ozone & weather - UV stabilised
- Flame resistant
- Can be cut to custom lengths
- Available in four thicknesses
- Indoor/outdoor use



PROFLEX PREMIUM NEOPRENE CONT.

	CODE (CUSTOM LENGTH PER M)	THICKNESS (MM)	WIDTH (MM)
25MM WIDE 	CRP1.5/25W	1.5	25
	CRP3/25W	3	25
	CRP4.5/25W	4.5	25
	CRP6/25W	6	25
50MM WIDE 	CRP1.5/50W	1.5	50
	CRP3/50W	3	50
	CRP4.5/50W	4.5	50
	CRP6/50W	6	50
75MM WIDE 	CRP1.5/75W	1.5	75
	CRP3/75W	3	75
	CRP4.5/75W	4.5	75
	CRP6/75W	6	75
100MM WIDE 	CRP1.5/100W	1.5	100
	CRP3/100W	3	100
	CRP4.5/100W	4.5	100
	CRP6/100W	6	100
150MM WIDE 	CRP1.5/150W	1.5	150
	CRP3/150W	3	150
	CRP4.5/150W	4.5	150
	CRP6/150W	6	150
200MM WIDE 	CRP1.5/200W	1.5	200
	CRP3/200W	3	200
	CRP4.5/200W	4.5	200
	CRP6/200W	6	200
300MM WIDE 	CRP1.5/300W	1.5	300
	CRP3/300W	3	300
	CRP4.5/300W	4.5	300
	CRP6/300W	6	300
1200MM WIDE 	CRP15W	1.5	1200
	CRP30W	3	1200
	CRP45W	4.5	1200
	CRP60W	6	1200

*Mat sizes may vary + / - 5%. All rolls are 10m long. A cutting fee applies to any cut length less than 10m.