

SUMMIT SUPER POLISH

STAGE 2

PRODUCT CODE: 815

DESCRIPTION AND PRODUCT BENEFITS:

As an advanced O.E.M polish, SUMMIT SUPER POLISH eliminates paint surface defects by permanently removing: fine flattening marks, slight paint imperfections, hazes, and holograms on all types of paintwork. SUMMIT SUPER POLISH uses Diminishing Abrasive Technology (DAT), leaving a mirrored glossy finish, unmatched by conventional polishes. For best results apply using a light cut or polishing pad.

DIRECTIONS OF USE AND APPLICATION:

1. Shake well before use. 2. Clean the painted surface. Remove scratches and imperfections by using SUMMIT SUPER COMPOUND (product code: 814). 3. Spread SUMMIT SUPER POLISH evenly over the pad surface and a small amount to the surface to be treated. 4. Position the pad flat on the vehicle surface and start the polishing machine. 5. With steady pressure, work over the surface with a dual action polisher until the swirl marks and imperfections in the paint are removed. (High-speed polishing at 1,000 to 1,500 RPM also works well to remove paint imperfections). 6. Remove residue with a microfiber cloth.

PRECAUTIONS:


Do not apply in direct sunlight. Do not mix with other chemicals. Keep from freezing.

HEALTH & SAFETY INFORMATION:

For further information on the safe handling, storage and precautions for use of this product, consult the Safety Data Sheet. Keep out of reach of children.

DISCLAIMER:

As the actual conditions of use are out of our control no liability is accepted for any loss or damage caused directly or indirectly through the use of our products. Intending users should satisfy themselves, by carrying out appropriate tests, as to the suitability of this product for any particular purpose.



TYPICAL DATA:

APPEARANCE: Viscous blue- grey paste.

SPECIFIC GRAVITY: ~1.1 g/ml

ODOUR: Petroleum distillate.

PH: ~ 8.0

SOLUBILITY: Partially water soluble.

FLASH POINT: > 100°C

AVAILABLE SIZES:



A81510 - BOTTLE - 946 ML / 1 US QUART

