

empack
spraytech inc.

Empack Spraytech Inc.
98 Walker Drive
Brampton, Ontario, L6T 4H6
Canada
905-792-6571

PRODUCT: Emzone Odorstop (New Car) - 156 g

CODE: P6-044213

SECTION 01: IDENTIFICATION

Product Identity..... Emzone Odorstop (New Car) - 156 g
Product Item Numbers..... P6-044213
Manufacturer..... Empack Spraytech Inc.
98 Walker Drive
Brampton
Ontario
Canada
L6T 4H6
905-792-6571
24 hour emergency telephone number..... CANUTEC: 1-613-996-6666.
Recommended Use..... Deodorizer.

SECTION 02: HAZARD IDENTIFICATION



Label Elements:
Signal Word..... WARNING.
Hazard Classification:
Physical Hazards..... Flammable Aerosols - Category 2. Gases Under Pressure - Liquefied Gas.
Health Hazards..... Skin Irritation - Category 2. Eye Irritation - Category 2B. Specific Target Organ Toxicity, Single Exposure - Category 3.
Precautionary Statements:
Hazard Statement..... H223:Flammable aerosol. H229:Pressurised container: may burst if heated (2).
H280:Contains gas under pressure; may explode if heated (L). H315:Causes skin irritation. H320:Causes eye irritation. H335:May cause respiratory irritation.
Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use. P264:Wash hand thoroughly after handling. P280:Wear protective gloves. P261:Avoid breathing dust/fume/gas/mist/vapours/spray. P271:Use only outdoors or in a well-ventilated area.
Response..... P302+P352:IF ON SKIN: Wash with plenty of water. P332+P313:If skin irritation occurs: Get medical advice/attention. P362+P364:Take off contaminated clothing and wash it before reuse. P321:For specific treatment see section 4 on this SDS.
P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313:If eye irritation persists: Get medical advice/attention. P304+P340:IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312:Call a POISON CENTER if you feel unwell.
Storage..... P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F.
P403+P233:Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.
Disposal..... P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.
Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Ethyl alcohol	64-17-5	45-70
1,1-Difluoroethane	75-37-6	30-60
Non-Hazardous		
Odor neutralizer	Proprietary	1-5
Fragrance	Mix	0.1-1

PRODUCT: Emzone Odorstop (New Car) - 156 g**CODE: P6-044213****SECTION 04: FIRST-AID MEASURES**

Inhalation.....	Supply fresh air if any irritations persists.
Eye Contact.....	Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Get medical attention if irritation persists.
Skin Contact.....	Remove contaminated clothing. Launder clothing before reuse. Wash thoroughly with soap and lukewarm water.
Ingestion.....	Not likely to be ingested. If occurs, do not give anything by mouth to an unconscious person. Do not induce vomiting, get medical attention. Obtain medical advice.
Most important symptoms/effects, acute .. and delayed	Direct eye contact may cause temporary eye irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media.....	Dry chemical powder. Carbon dioxide. Foam, water spray or fog.
Unsuitable Extinguishing Media.....	None in particular.
Specific Hazards Arising from the Chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special Protective Equipment and Precautions for Firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from immediate hazard area if it is safe to do.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures Methods and Materials for Containment .. and Cleaning Up	Ensure adequate ventilation; avoid formation of dust. Wear protective equipment and keep unprotected persons away. Use respiratory protection against the effects of dust. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.
Environmental Precautions.....	Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling.....	Wash thoroughly after handling . Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Avoid contact with eyes. Avoid breathing vapours or spray mists of this product. Contents under pressure. Use with adequate ventilation. Keep away from heat, sparks, and open flames.
Conditions for Safe Storage including any Incompatibilities	Store in a cool, dry, well-ventilated area away from incompatible substances. Do not store in direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10). Store at temperature below 50°C (120°F).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Ethyl alcohol	Not established	1,000 ppm (15 minutes)	1,000 ppm	Not established	1,000 ppm	
1,1-Difluoroethane	Not available	Not available	Not available	Not available	Not available	Not available
Odor neutralizer	Not available	Not available	Not available	Not available	Not available	Not available
Fragrance	Not established	Not established	Not established	Not established	Not established	Not established
Appropriate Engineering Controls.....	Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Ground all equipment and cylinders before use.					
Individual Protection Measures:						
Eye/Face Protection.....	Prevent eye contact, wear safety glasses in the event that eye contact is possible.					
Skin Protection.....	Not normally required.					
Respiratory Protection.....	Not required on a short-term basis or if exhaust ventilation is provided. Use approved NIOSH respirators for emergencies.					

PRODUCT: Emzone Odorstop (New Car) - 156 g

CODE: P6-044213

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Thermal Hazards..... None Known.
 General Hygiene Considerations..... When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical State..... Aerosol.
 Physical Appearance..... Fine mist.
 Odour..... Fragrance.
 Odour Threshold (ppm)..... Not available.
 pH..... Not applicable.
 Vapour Pressure (psig)..... 58.
 Vapour Density (Air=1)..... >1.
 Evaporation Rate (n-Butyl Acetate = 1)..... Not available.
 Boiling Point (propellant), ° C..... -25.
 VOC Content..... No data.
 Specific Gravity (Liquid)..... 0.793.
 Specific Gravity (Aerosol)..... 0.845.
 Solubility in water..... Not available .
 Auto Ignition Temperature (°C)..... 440. (Propellant).
 Flash Point (°C), Method..... -50. Closed cup. (Propellant).
 Lower Explosive Limit (% vol)..... 4.32. (Propellant).
 Upper Explosive Limit (% vol)..... 17.35. (Propellant).

SECTION 10: STABILITY AND REACTIVITY

Reactivity Product not reactive under normal conditions of use.
 Chemical Stability..... Stable at normal temperatures and pressures.
 Possibility of Hazardous Reactions..... Will not occur.
 Conditions to Avoid..... Avoid sources of heat and flame, and electrostatic charge.
 Incompatible Materials..... Avoid contacting with oxidizers.
 Hazardous Decomposition Products..... Thermal decomposition and burning may produce carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Ethyl alcohol	39 mg/L (Mouse - 4hrs)	7,060 mg/kg (Oral - Rat); 20,000 mg/kg (Dermal - Rabbit)
1,1-Difluoroethane	176 mg/L (Rat - 4 hrs)	Not available
Odor neutralizer	Not available	Not available
Fragrance	No data	No data
Information on Likely Routes of Exposure:		
Routes of entry - Inhalation.....	Yes.	
Routes of entry - Skin & Eye.....	Yes.	
Routes of entry - Ingestion.....	No.	
Routes of entry - Skin Absorption.....	No.	
Symptoms Related to the Physical,	Irritant effects.	
Chemical and Toxicological Characteristics		
Acute Toxicity.....	May be harmful if swallowed.	
Skin Corrosion/Irritation.....	Causes mild skin irritation. Prolonged contact may be more irritating.	
Serious Eye Damage/Eye Irritation.....	Direct contact with eyes causes temporary irritation.	
Respiratory or Skin Sensitization.....	Inhalation may cause respiratory tract irritation. May cause skin sensitization.	
Germ Cell Mutagenicity.....	No information is available, and no adverse effects are expected.	
Carcinogenicity.....	Not classified as carcinogenic by ACGIH, IARC, OSHA or NTP.	
Reproductive Toxicity.....	This product is not expected to cause reproductive or developmental effects.	
STOT - Single Exposure.....	Specific target organ toxicity single exposure Category 3. May cause respiratory irritation.	
STOT - Repeated Exposure.....	Not classified.	
Aspiration Hazard.....	No data available .	
Chronic Effects.....	No long term chronic effects are known or anticipated.	

PRODUCT: Emzone Odorstop (New Car) - 156 g

CODE: P6-044213

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... This product contains the following substances which is hazardous for the environment:
 1,1-difluoroethane: Fish (Various) LC50-295.783 mg/l (96h), Daphnia magna
 EC50-146.695 mg/l (48h). Ethyl alcohol (CAS#: 64-17-5): Toxicity to fish: LC50 14200
 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 9300 mg/L, 48 hrs; Toxicity to algae:
 not available.

Persistence and degradability The product itself has not been tested.

Bioaccumulation Potential..... The product itself has not been tested.

Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

DOT (US-Road)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D.

IMDG (International- Marine)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

IATA (International- Air)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

SECTION 15: REGULATORY INFORMATION

Canada Regulations:..... Refer to Section 2 for a WHMIS 2015 Classification for this product.

US Regulations..... OSHA (29CFR 1910.1200). This product is considered hazardous under the OSHA Hazard
 Communication Standard.

SECTION 16: OTHER INFORMATION

Disclaimer..... The information contained herein is based on data considered accurate. No guarantee or
 warranty is expressed or implied regarding the accuracy of this data or the results obtained
 from the use thereof. The SDS provider assumes no responsibility for personal injury or
 property damage to vendors or users or third parties, caused by the material. Such vendors
 or users assume all risks with the use of the material. This product has been classified in
 accordance with the hazard criteria of the CPR and the SDS contains all the information
 required by the CPR. .

Abbreviations..... ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical
 Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA:
 Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act
 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV:
 Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous
 Materials Information System STOT: Specific Target Organ Toxicity.

Prepared by Regulatory Affairs

Latest Revision 2019-07-19