according to Regulation (EC) No. 1907/2006, 2015/830

Perfumes for interiors FOEN "NEW CAR LEATHER"

Date: 31.07.2019 Version EN: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Perfumes for interiors FOEN "NEW CAR LEATHER"

1.2. Relevant identified uses of the substance or mixture and uses advised againstIdentified uses:Air FreshenerUses advised against:none

1.3. Details of the supplier of the safety data sheet

FOEN SCENT Sp. z o.o. ul. Krakowska 29D 50-424 Wrocław Tel. (+48) 600305308 E-mail address of the person responsible for data sheet: <u>info@foen.pl</u>

1.4. Emergency telephone

112 (general emergency telephone number)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Acc. to 1272/2008 Flam. Liq. 3; H226

Human health dangers: None. Environmental hazards: None. Physic-chemical hazards: Flammable liquid and vapour.

2.2. Label elements Pictograms:



Signal Word: Warning

Hazard Statement: H226 – Flammable liquid and vapour.

Precautionary Statement:

P102 – Keep out of reach of children
P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P403+P235 – Store in a well-ventilated place. Keep cool.
P501 – Dispose of contents/container to an authorized waste disposal plant

EUH208: Contains Linalool, 4-tert-butylcyclohexyl acetate, cis-4-(propan-2-yl)cyclohexyl]metanol, 3-p-cumenyl-2methylpropionaldehyde, 4-(4-hydroxy-4-methylpentyl)cyclohex-3-ene-1-carbaldehyde. May produce an allergic reaction.

2.3. Other hazards

The mixture does not contain any substances PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

according to Regulation (EC) No. 1907/2006, 2015/830

Perfumes for interiors FOEN "NEW CAR LEATHER"

Date: 31.07.2019 Version EN: 1.0

3.2. Mixtures

Hazardous components:

	contains	Classification 1272/2008	
Substance name	%	Hazard Class and Category Code(s)	Hazard Statement Code(s)
Ethanol ^{* ⁽¹⁾} CAS: 64-17-5 EINECS: 200-578-6 Index No.: 603-002-00-5 REACH No.: 01-2119457610-43-XXXX	<50	Flam. Liq. 2 Eye Irrit. 2	H225 H319
Linalool CAS: 78-70-6 EINECS: 201-134-4 Index No.: 603-235-00-2 REACH No.: 01-2119474016-42-XXXX	<0,5	Skin Sens. 1B	H317
4-tert-butylcyclohexyl acetate CAS: 32210-23-4 EINECS: 250-954-9 Index No.: - REACH No.: 01-2119976286-24-XXXX	<0,5	Skin Sens. 1B	H317
cis-4-(propan-2-yl)cyclohexyl]metanol CAS: 13828-37-0 EINECS : 237-539-8 Index No. : - REACH No.: 01-2119983532-32-XXXX	<0,5	Skin Sens. 1B	H317
3-p-cumenyl-2-methylpropionaldehyde CAS: 103-95-7 EINECS: 203-161-7 Index No.: - Nr REACH: 01-2119970582-32-XXXX	<0,5	Skin Irrit. 2 Skin Sens. 1 Aquatic Chronic 3	H315 H317 H412
Benzyl alcohol* CAS: 100-51-6 EINECS: 202-859-9 Index No.: 603-057-00-5 REACH No.: 01-2119492630-38-XXXX	<0,5	Acute Tox. 4 Eye Irrit. 2	H302 H332 H319
4-(4-hydroxy-4-methylpentyl)cyclohex-3- ene-1-carbaldehyde CAS: 31906-04-4 EINECS: 250-863-4 Index No.: - REACH No.: 01-2119489989-04-XXXX	<0,5	Skin Sens. 1	H317

Full text of H-phrases in Section 16

* Substance with the highest concentration of occupational exposure allowed at national level.

⁽¹⁾ specific concentration limits: Eye Irrit. 2; H319: >50%

according to Regulation (EC) No. 1907/2006, 2015/830

Perfumes for interiors FOEN "NEW CAR LEATHER"

Date: 31.07.2019 Version EN: 1.0

SECTION 4: First aid measures

4.1. Description of first aid measures

Skin contact:

Take off contaminated clothing. Wash skin with soap and water. In case of irritation, contact a physician Eye contact:

Contaminated eyes rinse with open eyelids. Consult a doctor.

Inhalation:

Remove to fresh air. Consult a doctor.

Ingestion:

Rinse mouth with water. Do not induce vomiting! Obtain medical attention. Do not give anything by mouth to unconscious people.

4.2. Most important symptoms and effects, both acute and delayed

The product contains allergens that may cause allergic reactions in contact with the skin.

4.3. Indication of any immediate medical attention and special treatment needed

The decision about how to proceed is made by the doctor after a thorough assessment of the victim.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: dry powder extinguishers, water spray. Use appropriate extinguishing method for conditions.

Unsuitable extinguishing media: Do not use a direct water jet.

5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour. During the fire, can be released toxic decomposition products.

5.3. Advice for firefighters

In the event of a fire in a confined space should wear protective clothing and breathing apparatus with compressed air. Do not allow fire-fighting water run-off into surface water, groundwater and sewer.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: notify the appropriate service. Reduce access to the area of failure until the relevant cleaning operations have been completed. Remove all sources of ignition. *For emergency responders:* Ensure adequate ventilation. Avoid skin and eye contamination.

6.2. Environmental precautions

Do not allow large amounts of this product to enter drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Prevent leakage and absorb with inert, absorbent material. The contaminated material is placed in properly labeled containers for disposal in accordance with applicable regulations.

6.4. Reference to other sections

Refer to protective measures listed in section 8. Refer to disposal considerations listed in section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with eyes and skin.

Avoid sources of ignition, high temperature, hot surfaces and open fire.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area in a properly labeled tightly sealed original container. Keep away from heat and hot surfaces. Avoid direct sunlight and sources of heat, hot surfaces and open flames.

according to Regulation (EC) No. 1907/2006, 2015/830

Perfumes for interiors FOEN "NEW CAR LEATHER"

Date: 31.07.2019 Version EN: 1.0

Do not store together with foodstuffs, beverages and animal feeds.

7.3. Specific end use(s)

Air Freshener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

Substance	Ethanol
CAS No.	64-17-5

	Limit value - Eight hours		Limit value - Short term		
	ppm	mg/m³	ppm	mg/m³	
Australia	1000	1880			
Austria	1000	1900	2000	3800	
Belgium	1000	1907			
Canada – Ontario			1000		
Canada – Québec	1000	1880			
Denmark	1000	1900	2000	3800	
Finland	1000	1900	1300 (1)	2500 (1)	
France	1000	1900	5000	9500	
Germany (AGS)	200	380	800 (1)	1520 (1)	
Germany (DFG)	200	380	800 (1)	1520 (1)	
Hungary		1900		7600	
Ireland			1000 (1)		
Latvia		1000			
New Zealand	1000	1880			
Poland		1900			
Romania	1000	1900	5000 (1)	9500 (1)	
Singapore	1000	1880			
South Korea	1000	1900			
Spain			1000	1910	
Sweden	500	1000	1000 (1)	1900 (1)	
Switzerland	500	960	1000	1920	
The Netherlands		260		1900	
USA – NIOSH	1000	1900			
USA – OSHA	1000	1900			
United Kingdom	1000	1920			
	Remarks				
Finland	(1) 15 minutes average value				
Germany (AGS)	(1) 15 minutes average value				
Germany (DFG)	(1) 15 minutes average value				
Ireland	(1) 15 minutes reference period				

according to Regulation (EC) No. 1907/2006, 2015/830

Perfumes for interiors FOEN "NEW CAR LEATHER"

Date: 31.07.2019 Version EN: 1.0

Romania	(1) 15 minutes average value
Sweden	(1) 15 minutes average value

Substance	Benzyl alcoho	Benzyl alcohol				
CAS No.	100-51-6					
	Limit value - E	Eight hours	Limit value - Short term			
	ppm	mg/m³	ppm	mg/m³		
Finland	10	45				
Germany (AGS)	5 (1)	22 (1)	10 (1)(2)	44 (1)(2)		
Germany (DFG)	5 (1)	22 (1)	10 (1)(2)	44 (1)(2)		
Latvia		5				
Poland		240				
Switzerland	5	22				
	Remarks					
Germany (AGS)	(1) Inhalable f	(1) Inhalable fraction and vapour (2) 15 minutes average value				
Germany (DFG)	(1) Inhalable f	(1) Inhalable fraction and vapour (2) 15 minutes average value				

<u>Ethanol</u>

DNEL worker, inhalation, long-term, systemic: 950 mg/m³ DNEL worker, inhalation, short-term, systemic: 1900 mg/m³ DNEL worker, dermal, long-term, systemic: 343 mg/kg/day DNEL consumer, inhalation, long-term, systemic: 114 mg/m³ DNEL consumer, inhalation, short-term, systemic: 950 mg/m³ PNEC fresh water: 0,96mg/l PNEC marine water: 0,79mg/l PNEC intermediate release: 2,75mg/l PNEC STP: 580mg/l PNEC sediment fresh water: 3,6mg/kg PNEC soil: 0,63mg/kg

8.2. Exposure controls Engineering controls:

No special recommendations. Good ventilation is recommended.

Individual protection measures, such as personal protective equipment:

Eye protection: Not required. Avoid eye contact. Skin protection: Hands: Not required. Avoid contact with skin. Wash your hands after use Other: It is not required. Respiratory Protection: It is not required.

Thermal hazards: Not applicable. Environmental exposure controls:

Prevent the spread large quantities in the environment and enter drains and watercourses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

• Appearance: Liquid

according to Regulation (EC) No. 1907/2006, 2015/830

Perfumes for interiors FOEN "NEW CAR LEATHER"

Date: 31.07.2019 Version EN: 1.0

- Odour: Characteristic, pleasant
- Odour threshold; not specified
- pH: not specified
- Melting point/freezing point; not specified
- Initial boiling point and boiling range; 78°C (ethanol)
- Flash point; >23°C
- Evaporation rate; not specified
- Flammability (solid, gas); not flammable
- Upper/lower flammability or explosive limits; 3,3%vol. / 19%vol. (ethanol)
- Vapour pressure; 59hPa at 20°C (ethanol)
- Vapour density; not specified
- Relative density; ap. 0,9
- Solubility(ies); miscible in water
- Partition coefficient: n-octanol/water; not specified
- Auto-ignition temperature; 425°C (ethanol)
- Decomposition temperature; not specified
- Viscosity; not specified
- Explosive properties; not specified
- Oxidising properties: not specified

9.2. Other information

No other information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is not reactive.
10.2. Chemical stability
Stable under normal conditions of use, storage and transport.
10.3. Possibility of hazardous reactions
None.
10.4. Conditions to avoid
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
10.5. Incompatible materials
Strong oxidizers.
10.6. Hazardous decomposition products

No hazardous decomposition products under normal conditions of use and storage.

As a result of thermal decomposition, carbon oxides are released.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

(a) acute toxicity: based on the available data, the classification criteria are not met

(b) skin corrosion/irritation: based on the available data, the classification criteria are not met

(c) serious eye damage/irritation: based on the available data, the classification criteria are not met

(d) respiratory or skin sensitization: based on the available data, the classification criteria are not met

(e) germ cell mutagenicity: based on the available data, the classification criteria are not met

(f) carcinogenicity: based on the available data, the classification criteria are not met

(g) reproductive toxicity: based on the available data, the classification criteria are not met

(h) STOT-single exposure: based on the available data, the classification criteria are not met

(i) STOT-repeated exposure: based on the available data, the classification criteria are not met

(j) aspiration hazard: based on the available data, the classification criteria are not met

<u>Ethanol</u>

LD50 (oral, rat): 7060mg/kg LD50 (oral, mouse): 3450mg/kg LD50 (oral, rabbit): 6300mg/kg LC50 (inhalation, rat): 20000ppm, 10h LC50 (inhalation, mouse): 39mg/m³, 4h

according to Regulation (EC) No. 1907/2006, 2015/830

Perfumes for interiors FOEN "NEW CAR LEATHER"

Date: 31.07.2019 Version EN: 1.0

SECTION 12: Ecological information

12.1.Toxicity

Mixture not classified as dangerous for the environment. <u>Ethanol</u> Fish (Oncorchynhus mykiss) LC50: 12900 - 15300mg/l, 96h Microorganisms (Ps. putida): EC50: 34900mg/l, 5-30min.

12.2. Persistence and degradability

No date available.

12.3. Bioaccumulative potential

No date available.

12.4. Mobility in soil

No date available.

12.5. Results of PBT and vPvB assessment

Substances in the mixture do not meet the criteria for classification as PBT or vPvB in accordance with Annex XIII of REACH.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

<u>Recommendations for the product:</u> Small quantities can be disposed with household waste. Dispose of in accordance with local regulations.

<u>Recommendations for used packaging:</u> Recycle / dispose of packaging waste in accordance with applicable regulations.

Waste codes:

14 06 03* Other solvents and solvent mixtures 15 01 02 Plastic packaging

Directive 2008/98/EC Of The European Parliament And Of The Council of 19 November 2008 on waste and repealing certain Directives

SECTION 14: Transport information

14.1. UN number ADR/RID/IMDG/IATA: 1993

14.2. UN proper shipping name ADR/RID/IMDG: FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL) IATA: Flammable liquid, n.o.s. (Ethanol)

14.3. Transport hazard class(es) ADR/RID/IMDG/IATA: 3

Label: 3



14.4. Packing group ADR/RID/IMDG/IATA: III

according to Regulation (EC) No. 1907/2006, 2015/830

Perfumes for interiors FOEN "NEW CAR LEATHER"

Date: 31.07.2019 Version EN: 1.0

14.5. Environmental hazards

ADR/RID/IMDG/IATA: no

14.6 Special precautions for user Hazard identification number: 33 EmS: F-E, S-E

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Other information: ADR:

Limited quantities LQ: 5L

· Excepted quantities EQ: E1

Transport category: 3

Code Tunnel restriction: D/E

IMDG

· Limited quantities (LQ): 5L

· Excepted quantities (EQ) Code: E1

UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL)), 3, III

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU REGULATIONS:

- Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
- Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- 3. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Text with EEA relevance).
- 4. Directive 2008/98/EC Of The European Parliament And Of The Council of 19 November 2008 on waste and repealing certain Directives

15.2. Chemical safety assessment

No chemical safety assessments for the mixture.

- List of substances subject to authorization (REACH; Annex XIV): not applicable

- Candidate list of SVHCs: not applicable

- Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (REACH; Annex XVII): not applicable

SECTION 16: Other information

Abbreviations and acronyms, list of relevant hazard statements used in the safety data sheet:

H225 – Highly flammable liquid and vapour

H226 – Flammable liquid and vapour.

- H302 Harmful if swallowed
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation

according to Regulation (EC) No. 1907/2006, 2015/830

Perfumes for interiors FOEN "NEW CAR LEATHER"

Date: 31.07.2019 Version EN: 1.0

H332 - Harmful if inhaled. H412 - Harmful to aquatic life with long lasting effects Flam. Liq. 2 - Flammable liquid cat. 2 Flam. Liq. 3 – Flammable liquid cat. 3 Acute Tox. 4 – Acute toxicity cat. 4 Skin Irrit. 2 - Skin irritation cat. 2 Skin Sens. 1 - Skin sensitization cat. 1 Skin Sens. 1B - Skin sensitization cat. 1B Eye Irrit. 2 - Eye irritation cat.2 Aquatic Chronic 3 - Hazardous to the aquatic environment cat. 3 **DNEL –** Derived No-Effect Level **PNEC –** Predicted No-Effect Concentration LD50 - lethal dose LC50 – lethal concentration EC50 - effective concentration PBT - Persistent, Bioaccumulative and Toxic vPvB - very Persistent and very Bioaccumulative ADR – International Carriage of Dangerous Goods by Road RID – International Carriage of Dangerous Goods by Rail **IMDG** – International Maritime Dangerous Goods ICAO – Safe Transport of Dangerous Goods by Air

Classification procedure: Flash point value

Training:

Before working on the product, please read the safety rules regarding the handling of chemicals, and in particular take proper workplace training. Persons working on hazardous materials transport under ADR should be adequately trained in their duties (general, occupational and safety).

RESOURCES

Annex to Regulation (EU) 2015/830. Current legislation (Section 15). Information Agency for Chemical Substances.

The information in this MSDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this MSDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.