

Premium Protective Film

Q1

Q1® Premium Protecting Film is a clear HDPE protective sheet treated to ensure paint adhesion of both solvent and waterborne paints specific for vehicle painting jobs.

It has an excellent paint adhesion due to its electrostatic property result of corona treatment and the composition of the raw material with specific additives.

Q1® Premium Masking film clings to vehicles and has centred printing to help with alignment.



Features

- Corona treatment to obtain maximum adhesion of paint
- Translucent to assist in the moving of vehicles
- Sheeting clings to the vehicle and has centred printing to help with alignment
- Excellent adhesion
- Temperature rating +230°F / 110°C
- Solvent resistant
- Easy roll release

Benefits

- Paint absorbent
- Resists tearing
- Resistant to solvents
- No bleed-through
- Easy to use dispenser box – Fast Application
- Statically charged for easy masking

Available Colour

Clear

Temperature Resistance

230°F / 110°C

Product Reference

Part#	EU Size	Pcs/ Case
PFO24	4 m x 150 m	1 roll/ box
PFO34	4 m x 300 m	1 roll/ box
PFO25	5 m x 120 m	1 roll/ box
PFO26	6 m x 110 m	1 roll/ box
Part#	US Size	Pcs/ Case
PFO12	12ft x 400ft/ 3.66m x 122m	1 roll/ box
PFO16	16ft x 350ft/ 4.9m x 107m	1 roll/ box

Technical Data Sheet

Properties	Measuring Units	Value	Measuring method
Density	g/cm ³	0.95	Following
Thickness	µm	8 microns	Following
Tensile strenght <i>machine direction</i>	N/mm ²	70	Following
Tensile strenght <i>transverse direction</i>	N/mm ²	28	Following
Elongation at break <i>machine direction</i>	%	422	Following
Elongation at break <i>transverse direction</i>	%	893	Following
Dart drop	g/µm	3.45	Following
Temperature stability	°F/ °C	230/ 110	

Additional Information**Storage & Handling**

Q1® Premium Masking Solutions must be stored in a dry location, protected from direct sunlight exposure and from freezing. Storage temperatures should be as close as possible to room temperature; suggested storage temperature should range from 59°F / 15°C to 77°F / 25°C with max. relative humidity of 50%. Do not store tapes and related products in the paint booth during bake cycles.

Make sure the surface you wish to place the tape on is cleaned, dried and free from oil and dust. It is suggested not to apply the tape with temperatures lower than 50°F / 10°C. With a storage temperature lower than 50°F / 10°C, it is always suggested temperature reconditioning of the tape at room temperature (79°F / 15°C - 59°F / 25 °C) before its use. We always recommend testing material in relation to the required applications.

Shelf life from date of manufacture

No yellowing and < 10% loss in performance at 73.4°F / 23 °C, 50% humidity is considered 12 months Q1® Premium Masking Solutions does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.

Technical Information Disclaimer

The technical information, suggestions and other statements contained in this documents have been compiled for your guidance and usage. Information is based on experience and tests that Q1® Premium Masking Solutions believe are reliable. The accuracy or completeness of such information is not guaranteed. Q1® Premium Masking Solutions has no control about conditions in which products are used, stores or handles. The above information doesn't constitute a warranty.

Product Use

Q1® would advise that there are many factors beyond Q1® control but within the users knowledge that can affect the use and performance of Q1® products. Q1® remind the user of the products to make sure that its range is used as per the instructions printed above. It is the users sole responsibility to determine that all preparation has been correctly carried out and that the working conditions are as per Q1® literature.

CARISMATIX SRL

Via dei Laghi, 24 - 36077 Altavilla Vicentina (VI)

P.IVA 04201310242

info@carimatix.it

+39 0444 1323970

