

LED PL : DUAL MODE REPLACEMENT LAMPS

DESCRIPTION

LED PL Replacement Lamps directly replace fluorescent PL lamps at a fraction of the energy cost.

FEATURES

- Dual mode: operates on existing ballasts or line voltage
- Lasts 5x longer than compact fluorescent lamps
- Consumes up to 1/3 the energy of conventional CFL
- Base rotates for precision orientation once installed in fixture
- Shatter-resistant for reduced risk of injury and breakage
- Instant-on with no warmup, unlike CFLs
- Suitable for use in 6" cans
- Non-dimmable
- 12W items not for use in totally enclosed luminaires

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Commercial/Residential
- Hotel/Hospitality
- Education
- Healthcare
- Retail
- Property Management



RoHS
Compliant

cUL[®] US

CLASSIFIED
cUL[®] US

PERFORMANCE	Power Consumption	5W	7W	12W
	Lumens	475/500	700	1,100
	Efficacy (LPW)	95/100	100	92
	CRI	80+		
	Beam	140°		
	CCT	2700K, 3000K, 3500K, 4000K		
	Life (L70)	50,000 hours		
ELECTRICAL	Power Factor	≥0.9		
	THD	<20%		
	Input Voltage	120-277V		
CONSTRUCTION	Operating Temperature	-20°C (-4°F) to 40°C (104°F)		
	Base	G23, GX23, G24Q, G24D, GX24Q		
LISTINGS	Certification(s)	cULus Classified		
	Material Usage	RoHS Compliant; no mercury or lead		
	Environment	UL/cUL Classified for damp locations		

PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Watts	CCT	CRI	MOL	Orientation	Base	Life/Hours	Replaces Fluor
10172	LED5W2P/G23/827DM-G7B	475	5W	2700K	80+	4.13"	Vertical	G23	50,000	13W CFL
10173	LED5W2P/G23/830DM-G7B	475	5W	3000K	80+	4.13"	Vertical	G23	50,000	13W CFL
10174	LED5W2P/G23/835DM-G7B	475	5W	3500K	80+	4.13"	Vertical	G23	50,000	13W CFL
10180	LED5W2P/G23/840DM-G7B	475	5W	4000K	80+	4.13"	Vertical	G23	50,000	13W CFL
09782	LED5W2PH/G23/835DM-G7B	500	5W	3500K	80+	4.13"	Horizontal	G23	50,000	13W CFL
09626	LED7W2PH/G23/835DM-G7	700	7W	3500K	80+	5.82"	Horizontal	G23	50,000	18W CFL
10176	LED7W2P/GX23/827DM-G7B	700	7W	2700K	80+	4.78"	Vertical	GX23	50,000	18W CFL
10177	LED7W2P/GX23/830DM-G7B	700	7W	3000K	80+	4.78"	Vertical	GX23	50,000	18W CFL
09904	LED7W2P/GX23/835DM-G7B	700	7W	3500K	80+	4.78"	Vertical	GX23	50,000	18W CFL
10178	LED7W2P/GX23/840DM-G7B	700	7W	4000K	80+	4.78"	Vertical	GX23	50,000	18W CFL
09627	LED7W2PH/GX23/835DM-G7	700	7W	3500K	80+	6.1"	Horizontal	GX23	50,000	18W CFL
10163	LED12W2PH/GX23/827DM-G7*	1,100	12W	2700K	80+	6.1"	Horizontal	GX23	50,000	26W CFL
10164	LED12W2PH/GX23/830DM-G7*	1,100	12W	3000K	80+	6.1"	Horizontal	GX23	50,000	26W CFL
09629	LED12W2PH/GX23/835DM-G7*	1,100	12W	3500K	80+	6.1"	Horizontal	GX23	50,000	26W CFL
10179	LED12W2PH/GX23/840DM-G7*	1,100	12W	4000K	80+	6.1"	Horizontal	GX23	50,000	26W CFL
10166	LED12W4PH/G24Q/827DM-G7*	1,100	12W	2700K	80+	5.82"	Horizontal	G24Q/GX24Q	50,000	26W CFL
10167	LED12W4PH/G24Q/830DM-G7*	1,100	12W	3000K	80+	5.82"	Horizontal	G24Q/GX24Q	50,000	26W CFL
09630	LED12W4PH/G24Q/835DM-G7*	1,100	12W	3500K	80+	5.82"	Horizontal	G24Q/GX24Q	50,000	26W CFL
10168	LED12W4PH/G24Q/840DM-G7*	1,100	12W	4000K	80+	5.82"	Horizontal	G24Q/GX24Q	50,000	26W CFL
10169	LED12W4PV/G24Q/827DM-G7*	1,100	12W	2700K	80+	3.78"	Vertical	G24Q/GX24Q	50,000	26W CFL
10170	LED12W4PV/G24Q/830DM-G7*	1,100	12W	3000K	80+	3.78"	Vertical	G24Q/GX24Q	50,000	26W CFL
09631	LED12W4PV/G24Q/835DM-G7*	1,100	12W	3500K	80+	3.78"	Vertical	G24Q/GX24Q	50,000	26W CFL
10171	LED12W4PV/G24Q/840DM-G7*	1,100	12W	4000K	80+	3.78"	Vertical	G24Q/GX24Q	50,000	26W CFL
10473	LED12W2PH/G24D/835DM-G7	1,100	12W	3500K	80+	5.82"	Horizontal	G24D	50,000	26W CFL
10474	LED12W2PH/G24D/840DM-G7	1,100	12W	4000K	80+	5.82"	Horizontal	G24D	50,000	26W CFL

NOTE: Use order code when ordering. Visit eiko.com for complete ballast compatibility information. Not for use with emergency ballasts.

*Not for use in totally enclosed luminaires (12W only).

DIMENSIONS

