

Prepared on the basis of EU regulation 1907/2006 (REACH)

## Safety data sheet

Developed: 18-11-2021

SDS version: 1.7

---

### ITEM 1: Identification of the substance/mixture and of the company/company

---

#### 1.1. Product identifier

Trade name: SPECIAL THINNER S 17

Product number.: -

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Recommended uses:

Spray thinner for thinning enamel and primers as well as industrial paints for spraying.

Uses advised against: May only be used as described above, other uses must be made in consultation with the supplier.

#### 1.3. Details of the supplier of the safety data sheet

##### Company name and address:

Lars Frey Farve & Lak ApS

Solrødvej 6, port H,

DK-4621 Gadstrup

Denmark

Tlf: + 45 20 84 21 31

##### Contact person and email:

lfj@larsfrey.dk

##### The safety data sheet has been prepared and validated by:

mediator A/S, Centervej 2, 6000 Kolding. Consulent: DH

#### 1.4. Emergency phone

The Danish poison hotline: +45 82 12 12 12, or the poison line in your country and region

Prepared on the basis of EU regulation 1907/2006 (REACH)

## ITEM 2: Hazard identification

### 2.1. Classification of the substance or mixture

CLP (1272/2008): Flam. Liq. 3;H226, Acute Tox. 4;H312+H332, Skin Irrit. 2; H315. Wording of H-phrases - see below in item 16.

### 2.2. Marking elements



#### Signal word:

Warning

Flammable liquid and vapor. (H226)

Harmful in case of skin contact or inhalation. (H312+H332)

Causes skin irritation. (H315)

Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. No smoking. (P210)

Avoid inhalation of fumes/vapours. (P261)

Wear protective gloves/protective clothing/eye protection/face protection. (P280)

IF INHALED: Move the person to a place with fresh air and ensure that breathing is facilitated. Call the POISON LINE/doctor in case of discomfort. (P304+P340+P312)

In case of skin irritation: Seek medical attention. (P332+P313)

### 2.3. Other dangers

The product contains organic solvent. Repeated exposure to organic solvents can cause damage to the nervous system and internal organs such as liver, kidneys.

#### Other marking:

-

#### Other things

-

## ITEM 3: Composition of/information on ingredients

### 3.1./3.2. Substances / Mixtures

Ingredient	Index-no.	CAS/EC no.	CLP classification	w/w %	Note
Xylene	601-022-00-9	1330-20-7/ 215-535-7	Flam. Liq.3;H226, Acute Tox. 4;H312, H332, Skin Irrit. 2;H315	> 90	1

1 = The substance is included in the Norwegian Working Environment Authority's list of organic solvents.

Wording of H-phrases - see below in item 16.

Prepared on the basis of EU regulation 1907/2006 (REACH)

---

## **ITEM 4: First aid measures**

---

### **4.1. Description of first aid measures**

Inhalation:	Seek fresh air. Keep the casualty under supervision. In case of discomfort, call a POISON CENTER or a doctor.
Intake:	Rinse your mouth thoroughly and drink 1-2 glasses of water in small sips. Do not induce vomiting. Seek medical attention if discomfort continues.
Skin contact:	Remove contaminated clothing immediately. Wash the skin with soap and water. Seek medical attention in case of discomfort.
Eye contact:	If the product gets into the eyes, rinse with water (preferably from eyewash) until the irritation ceases. Seek medical attention if irritation persists.
Combustion:	Rinse with water until the pain stops. Remove clothing that has not been burned - seek medical advice/hospital, if possible continue rinsing until the doctor takes over the treatment.
Additional information:	When consulting a doctor, bring the safety data sheet or label.

### **4.2. Most important symptoms and effects, both acute and delayed**

Harmful by inhalation and skin contact.

Irritating effects: The product contains substances that are local irritants in case of skin/eye contact or inhalation. Contact with local irritants can result in the contact area becoming more exposed to the absorption of harmful substances such as allergens.

### **4.3. Indication of immediate medical attention and special treatment needed**

Show this safety data sheet to the doctor or emergency department.

---

## **ITEM 5: Fire fighting**

---

### **5.1. Extinguishing media**

Extinguish with powder, foam, carbon dioxide or water mist. Do not use a water jet as this can spread the fire.

### **5.2. Special hazards associated with the substance or mixture**

Flammable liquid and vapor. Avoid inhalation of vapors and fumes - seek fresh air. In case of fire, the product decomposes and dangerous gases such as COX can be formed. In case of fire, thick black smoke will be produced. Exposure to decomposition products can cause health damage. Cool closed containers exposed to fire with water. Do not let water from fire extinguishing run into sewers and streams.

### **5.3. Instructions for firefighters**

Firefighters should use appropriate protective equipment.

Prepared on the basis of EU regulation 1907/2006 (REACH)

## ITEM 6: Accidental release precautions

### 6.1. Personal safety measures, personal protective equipment and emergency procedures

Use personal protective equipment - see section 8. Avoid inhalation and contact with skin and eyes.

### 6.2. Environmental protection measures

Avoid unnecessary release to the environment - see section 12. Contact the authorities in connection with contamination of the soil and water environment as well as in the event of spills into sewers.

### 6.3. Methods and equipment for containment and purification

Spills are contained and collected with sand or other absorbent non-combustible material and transferred to suitable waste containers. Rinse afterwards with water. See point 13 for disposal.

### 6.4. Reference to other points

See above.

## ITEM 7: Handling and storage

### 7.1. Precautions for safe handling

See under section 8 for information on precautions for use and personal protective equipment. Smoking and use of open flames prohibited. The product should be used in well-ventilated conditions. There should be access to running water and eyewash.

### 7.2. Conditions for safe storage, including any incompatibilities

The product should be stored securely, out of the reach of children and not together with food, feed, medicines etc. Should be stored in tightly closed original packaging. Must be stored in a dry, cool and ventilated place. Store fireproof. The National Emergency Management Agency's technical regulations for flammable liquids must be strictly followed, including the rules for flammable storage.

### Fire hazard class and storage.

Fire hazard class II-1, one storage unit = 5 litres.

A maximum of 25 units may be stored without the approval of the fire authorities. Please be aware that there may be relaxations, cf. section 3.1.2. in the Ministry of Defence's Order No. 1639 of 6/12/2016 on flammable and combustible liquids.

### 7.3. Special uses

See application section 1.

## ITEM 8: Exposure controls/personal protective equipment

### 8.1. Control parameters

Limit values according to executive order no. 1426 of 28/06/2021 on limit values for substances and materials:

Ingredient		Note
Xylene	25 ppm – 109 mg/m <sup>3</sup>	E, H

E = The substance has an EC limit value. H = The substance can be absorbed through the skin.

### DNEL/PNEC-value:

DNEL - Xylene:

#### Workers

Inhalation - Chronic Systemic	221 mg/m <sup>3</sup>
Inhalation - Acute Systemic	442 mg/m <sup>3</sup>
Inhalation - Chronic Local	221 mg/m <sup>3</sup>
Inhalation - Acute Local	442 mg/m <sup>3</sup>
Dermal - Chronic Systemic	212 mg/kg bw/day

Prepared on the basis of EU regulation 1907/2006 (REACH)

**Consumers**

Inhalation - Chronic Systemic	65.3 mg/m <sup>3</sup>
Inhalation - Acute Systemic	260 mg/m <sup>3</sup>
Inhalation - Chronic Local	65.3 mg/m <sup>3</sup>
Inhalation - Acute Local	260 mg/m <sup>3</sup>
Dermal - Chronic Systemic	125 mg/kg bw/day
Oral - Chronic systemic	12.5 mg/kg bw/day

**PNEC – Xylene:**

Fresh water	0.327 mg/L
Intermittent releases (Freshwater)	0.327 mg/L
Sea water	0.327mg/L
Land	2.31 mg/kg soil dw

**8.2. Exposure control**

There is no exposure scenario for this product.

**Appropriate exposure control measures:**

Use protective equipment as indicated below. Wash hands before breaks, toilet visits and after work. Do not eat, drink or smoke while using this product.

**Personal protection:**



Respiratory protection:	Use approved mask with gas filter type A (brown - against organic vapours). The filters have a limited service life (must be changed). Read the manufacturer's instructions.
Protection of hands:	Use nitrile rubber protective gloves.
Eye/face protection:	Use safety glasses or a face shield.
Protection of skin:	Special work clothes must be used. Use possibly protective suit for prolonged work with the product.

**Measures to limit environmental exposure**

Make sure that when working with the product, there is damming material in the immediate vicinity. If possible, use waste trays during work.

Prepared on the basis of EU regulation 1907/2006 (REACH)

---

## ITEM 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance:	Liquid
Smell:	-
Odor threshold:	-
pH:	-
Melting point/Freezing point (°C):	-
Initial boiling point and boiling range (°C):	-
Flash point (°C):	27
Evaporation rate:	-
Flammability (solid, gas):	-
Upper/lower flammability or explosion limits (vol-%):	7 / 1.1
Vapor pressure (Pa):	-
Vapor density (air=1):	-
Relative density:	0.86
Solubility:	-
Partition coefficient: n-octanol/water:	-
Self-ignition temperature (°C):	-
Decomposition temperature (°C):	-
Viscosity:	-
Explosive properties:	-
Oxidizing properties:	-

### 9.2. Other information

Weight % org. Solvents:	-
VOC (g/l):	-

---

## ITEM 10: Stability and reactivity

### 10.1. Reactivity

No data.

### 10.2. Chemical stability

The product is stable when used in accordance with manufacturer's instructions. The vapors can ignite at temperatures above the flash point.

### 10.3. Risk of dangerous reactions

Vapors and air can form explosive mixtures.

### 10.4. Conditions to avoid

Avoid heating and contact with ignition sources.

### 10.5. Materials to avoid

Avoid contact with strong acids, strong bases, strong oxidizing agents and strong reducing agents.

### 10.6. Hazardous decomposition products

In case of fire or strong heating, the product splits and dangerous gases such as COX can be formed.

Prepared on the basis of EU regulation 1907/2006 (REACH)

---

## ITEM 11: Toxicological information

---

### 11.1. Information on toxicological effects

**Acute toxicity:** Harmful in contact with skin and by inhalation.

Substance	Exposure route	Type	Test	Result
Xylene	Oral	Rat	LD50	3523 mg/kg bw
Xylene	Inhalation	Rat	LC50/ 4 hours	6350 ppm

**Skin corrosion/irritation:** Irritating to the skin - may cause redness. Can be absorbed through the skin and cause symptoms such as dizziness and headache.

**Serious eye damage/eye irritation:** May cause eye irritation.

**Respiratory sensitization or skin sensitization:** The data base does not give rise to classification.

**Germ cell mutagenicity:** The data base does not give rise to classification.

**Carcinogenicity:** The data basis does not give rise to classification.

**Reproductive toxicity:** The data base does not give rise to classification.

**Single STOT exposure:** The product emits vapors from organic solvents that may cause drowsiness and dizziness. In high concentrations, the vapors can cause headaches and intoxication.

**Repeated STOT exposures:** Prolonged or repeated exposure through skin contact or inhalation of vapors can cause damage to the central nervous system.

**Aspiration hazard:** The data basis does not give rise to classification.

---

## ITEM 12: Environmental information

---

### 12.1. Toxicity

Substance	Test Duration	Type	Test	Result
Xylene	96 hours	Fish	LC50	2.6 mg/L
Xylene	73 hours	Algae	EC50	2.2 mg/L

### 12.2. Persistence and degradability

Substance	Degradability in the aquatic environment	Test	Result
Xylene	Yes	OECD Guideline 301 F	28 days: 90%

### 12.3. Bioaccumulative potential

Substance	Potentially bioaccumulative	LogPow	BCF
Xylene	No	3.15	-

### 12.4. Mobility in soil

Test data not available.

Prepared on the basis of EU regulation 1907/2006 (REACH)

#### 12.5. Results of PBT and vPvB assessment

The substance does not meet the criteria for PBT or vPvB.

#### 12.6. Other adverse effects

None.

### ITEM 13: Disposal

#### 13.1. Methods for waste treatment

The product is covered by the regulations on hazardous waste. Spills and waste are collected in closed and tight containers, which are disposed of via the municipal waste scheme for hazardous waste with the specifications below.

Chemical waste group	EAK- code	Waste type
C	08 01 11	Paint and varnish waste containing halogenated solvents or other dangerous substances
C	20 01 13	Solvents

#### Special marking:

-

#### Contaminated packaging:

Packaging with residual contents of the product is disposed of under the same conditions as the product.

### ITEM 14: Transport information

The product is covered by the regulations on the transport of dangerous goods by road and sea according to ADR and IMDG.

#### 14.1 - 14.4.

##### ADR

UN-no.	UN proper shipping name	Transport hazard class(es)	Packaging group
1307	Xylenes	3	III

##### IMDG

UN number	UN proper shipping name	Transport hazard class(es)	Packing group
1307	Xylenes	3	III

#### 14.5. Environmental hazards

-

#### 14.6. Special precautions for the user

-

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the

##### IBC Code

Not applicable.



Prepared on the basis of EU regulation 1907/2006 (REACH)

---

## **ITEM 15: Information on regulation**

---

### **15.1. Special regulations/specific legislation for the substance or mixture with regard to safety, health and the environment**

-

#### **Limitations of use:**

During a workplace assessment, it must be ensured that employees are not exposed to influences that could entail a risk during pregnancy or breastfeeding (cf. Norwegian Working Environment Authority's Executive Order no. 559 of 17/06/2004 on the performance of work).

Young people under the age of 18 may not professionally use or be exposed to the product. However, young people over the age of 15 are exempt from this rule if the product is included as a necessary part of an education. (cf., however, the Norwegian Working Environment Authority's Executive Order no. 239 of 06/04/2005 on youth work).

#### **Requirements for special education:**

-

#### **Other marking:**

**Code Number (1993): 5-3.**

**Product no.: 894615.**

#### **Sources:**

The Danish Working Environment Authority's order no. 301 of 13 May 1993 on determining code numbers, with subsequent amendments.

Order on work with substances and materials (chemical agents) - BEK no. 1793 of 18/12/2015.

The Danish Working Environment Authority's order no. 1049 of 30 May 2021 on youth work, with subsequent amendments.

Executive Order No. 1369 of 25 November 2015 on the marketing and labeling of volatile organic compounds in certain paints and varnishes as well as products for car refinishing.

Executive order no. 1075 of 24 November 2011 on classification, packaging, labelling, sale and storage of substances and mixtures, with subsequent amendments.

Executive Order No. 115 of 26 January 2017 of the Chemicals Act.

Order on special duties for manufacturers, suppliers and importers, etc. of substances and materials according to the Working Environment Act - BEK no. 1794 of 18/12/2015.

Executive order no. 1426 of 28/06/2021 on limit values for substances and materials.

Executive order no. 2159 of 09/12/2020 on waste, with subsequent amendments.

### **15.2. Chemical Safety Assessment**

None.

Udarbejdet på baggrund af EU forordning 1907/2006 (REACH)

---

**ITEM 16: Other information**

---

**Other information:****Sources:**

EU Regulation No. 1907/2006 (REACH).

EU regulation no. 1272/2008 (CLP), with later adaptations. EU Regulation No. 276/2010.

ECHA – The European Chemicals Agency.

**The full wording of the H sentences referred to in points 2+3:**

H226 - Flammable liquid and vapour.

H312 - Harmful in contact with skin.

H315 - Causes skin irritation.

H332 - Harmful by inhalation.

<b>Classification according to Regulation (EC) No. 1272/2008:</b>	
Flam. Liq. 3;H226	On the basis of experimental data
Acute Tox. 4;H312+H332	Calculation method
Skin Irrit. 2;H315	Calculation method

**Abbreviations and acronyms used in the safety data sheet:**

REACH: Registration, assessment and approval of and restrictions on chemicals. Regulation (EC) No. 1907/2006.

CLP: Regulation (EC) No. 1272/2008 on classification, labeling and packaging.

CAS No.: Chemical Abstracts Service number.

EC no.: EINECS and ELINCS number (see also EINECS and ELINCS).

DNEL: Derived No-Effect Level (Derived No-Effect Level).

PNEC: Predicted No Effect Concentration (Predicted No Effect Concentration).

STOT: Specific Target Organ Toxicity (Specific Target Organ Toxicity).

LD50: Lethal Dose for 50% of a test population.

LC50: Lethal concentration for 50% of a test population.

EC50: The effective substance concentration that causes 50% of the maximum response.

PBT: Persistent, Bioaccumulative and Toxic substance (Persistent, Bioaccumulative and Toxic).

vPvB: Very persistent and very bioaccumulative (Very Persistent and Very Bioaccumulative).

**Other things**

The information in this safety data sheet only applies to the product mentioned in point 1 and is not necessarily valid when used together with other products.

Color pigment composition.

FBL - Robin red pigment

RNP - Red pigment

3RS - Red pigment

Changes have been made in the following points:

**1-16 General Update.**

This safety data sheet replaces version:

**1.6** (20-04-2020).

---