



Protective
Coatings
Group

FORTiCEL™ 
25 YEAR WARRANTY
 Professionally Applied, Safe & Effective

Permanent Protection

FortiCel's protective barrier will provide unparalleled microbial growth inhibition on all treated construction surfaces thereby reducing the potential of mold growth.

Commercial and residential contractors know the benefits of FortiCel™ as an effective and valuable solution to provide long-lasting value that is warranted for a full 25 years.

Put FortiCel™ to the Test

FortiCel™ is a proprietary thin film paint coating which incorporates a registered mildewcide that inhibits the growth of molds and mildew on the coating. When FortiCel™ is properly applied*, the dried film coating minimizes the growth of mold on the coating itself.

FortiCel's protective barrier will provide unparalleled microbial growth inhibition on the paint film applied to construction surfaces.

This dried film will not wash off, or degrade over time, ensuring long term benefit of the film integrity. This means that the benefits of the FortiCel™ coating will remain intact even in the most challenging environments.

We are so confident in the ability of FortiCel™ and its benefits that we will warranty the coating for a full 25 years against degradation due to normal wear and weathering, and mold growth on the coating of the FortiCel™ film surface.



FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology.™ "The FBC System Compatible Logo, FBC™, FlowGuard Gold®, BlazeMaster®, Corzan®, and TempRite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.



Professionally Applied

FortiCel™ is applied by certified technicians through a spray on application that is not disruptive to the construction process. Once the building is dried-in, the FortiCel™ coating is applied to all chosen surfaces. Other tradesmen may continue working while the product is being applied but it is important to perform the application prior to insulation. FortiCel™ will dry in 20 minutes to an hour and will not wash off or degrade.

*For above ground use only.

FortiCel™ Protects All Interior Construction Surfaces like:

- Dimensional lumber
- Concrete
- Wall panels
- Steel studs
- Floor joists
- Plywood
- OSB
- Trusses