## **DECLARATION OF PERFORMANCE**

No. 64685-a-CPR\_2021.09.1

Unique identification code of the product-type	64685 - Eurothane Eurodeck	
Intended use/es	Thermal insulation for buildings	
Manufacturer	Recticel Ltd. – Enterprise Way, Meir Park – Stoke-On-Trent, ST3 7UN - UK	
System/s of AVCP	AVCP 3	
Harmonised standard	EN 13165:2012 + A2:2016	
Approved body/ies	Approved bodies testing laboratory No. NB 0836 determined the production type under system AVCP3.	

Essential characteristics	Performance (The letters 'NPD' (No Performance Determined) are indicated where no performance is declared.)	
D :		
Reaction to fire	Reaction to fire	F
Reaction to fire – end use	Reaction to fire – end use	NPD
Thermal resistance	Thermal resistance (R <sub>D</sub> in m <sup>2</sup> K/W)	1,35 for d <sub>N</sub> 30mm
		7,25 for d <sub>N</sub> 160mm
	Thermal conductivity (λ <sub>D</sub> in W/mK)	0,022
Thickness	d <sub>N</sub> : 30-160 mm	T2
Compressive strength	CS(10/Y)150	
Tensile strength/shear behaviour	Tensile strength perpendicular to faces:	NPD
-	Shear strength:	NPD
	Shear modulus:	NPD
Water permeability	Water absorption	
	- short term by partial immersion	NPD
	- long term by partial immersion	NPD
	- long term by total immersion	NPD
	Flatness after one-sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Direct airborne sound insulation	Sound absorption	NPD
index		
Continuous glowing combustion	No harmonized test method available	
Release of dangerous substances to	No harmonized test method available	
the indoor environment		
Durability of reaction to fire against heat, weathering, ageing /	Reaction to fire does not change with time	
degradation		
Dimensional stability under specified	48h, 70°C, 90% R.H.	NPD
temperature and humidity conditions	7011, 10 0, 30 /0 18.11.	IN D
	48h, -20°C	NPD
	1011, 20 0	5
Deformation under specified	40 kPa, 70°C, 168h	NPD
compressive load and temperature		
conditions		
Compressive creep		NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

at Wevelgem on September 1st 2021

Wim Giebens - Industrial Manager Recticel Building Insulation



