

GENIEMAT[®] FF17

ROLL-OUT FLOATING FLOORS



PATENTS: US 8,240,430 US 8,556,029 CA 2,500,956 CA 2,503,420

PRODUCT SPECIFICATION

PRODUCT NAME: GenieMat FF17

DESCRIPTION:

Robust dimpled rubber pad made from 92% recycled rubber content used when superior sound control is required in mechanical rooms, sound studios, home theatres, entertainment venues, medical facilities, exercise, gym, and dance floors, and commercial, industrial, and multifamily housing.

APPLICATION:

Shock absorbing and impact sound reducing pad to be used under gypsum, light-weight, full-weight concrete and other floating floor applications.

FEATURES AND BENEFITS:

- Significantly increases IIC and STC ratings
- Mold, bacteria, fungi, and water resistant
- Qualifies for LEED[®] points
- No potential mold-producing fibreglass
- Will not breakdown or move under load
- Easy to install, rolls out quickly, stays in place, and doesn't need to be adhered

DIMENSION:

Rollgood: 4' wide, 15' long (1.2 m wide, 4.6 m long)

THICKNESS:

2/3" (nom. 17 mm)

ROLL WEIGHT:

104 lb/roll (47 kg/roll)

ROLL AREA:

60 ft² (5.6 m²)

ROLLS/PALLET:

15

LEAD TIME:

2-3 weeks after receipt of order

CONTACT Us

For Your Project Specific Questions

UK +44 203 9846444 | **Asia Pacific** +65 8452 6865 | **Middle East** +971 4 813 5501

E. info@pliteq.co.uk

© Pliteq (UK) LTD. 2020.

0420 [®]™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.co.uk

GENIEMAT® FF17

ROLL-OUT FLOATING FLOORS

PATENTS: US 8,240,430 US 8,556,029 CA 2,500,956 CA 2,503,420

TECHNICAL DATA

SHEET WEIGHT:	8.3 kg/m ² (1.7 lb/ft ²)
DENSITY:	488 kg/m ³ (30.6 lb/ft ³)
LABORATORY IMPACT INSULATION CLASS (ASTM E492):	Specified floor-ceiling assembly must be tested in a NVLAP-certified laboratory and comply with ASTM standards.
FIELD IMPACT INSULATION CLASS (ASTM E1007):	Specified floor-ceiling assembly must meet requirement as stated by building code and/or acoustical consultant.
TEMPERATURE STABILITY:	-40°C to +80°C (-40°F to +176°F)

CONTACT Us

For Your Project Specific Questions

UK +44 203 9846444 | **Asia Pacific** +65 8452 6865 | **Middle East** +971 4 813 5501

E. info@pliteq.co.uk

© Pliteq (UK) LTD. 2020.

®™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.co.uk