



## **Installation Instructions**

Phone/Text (208) 881-0909  
Email: [info@mntntopsnowbike.com](mailto:info@mntntopsnowbike.com)

---

### **SNOWBIKE/SNOWMOBILE, TOW & FOOT-PEG KIT**

- **P/N:** 3022-5810-00
- **FITS:** All snowbikes and snowmobiles.
- **INCLUDES:** (1) Bag, (1) tow lead 15', (2) leads 44", (2) leads 74", (2) carabiners, (2) foot pegs 4".

*Notes: If you are setting this up to work on another brand snowbike kit other than a MTN.TOP you will need to prepare your bike to be able to install the foot pegs. See instructions for that below. If you are using this kit on a MTN.TOP kit then the holes for the pegs are already there. See pictures below for reference.*

#### **FOOT PEG INSTALL:**

1. Foot peg mounting for "non" MTN.TOP kits: You will need to drill a hole into the tunnel on each side to mount the foot peg to. You will want to position the hole up high on the tunnel and as far forward as you can. Drill hole with a 13/32" drill bit. The proper mounting location for reference on the MTN.TOP kits.
  - a. 13" back from factory foot peg.
  - b. 22" up from floor
2. Install foot peg with supplied bolts and washers. Thread on and tight by hand. No need to make them any tighter than that unless you plan to keep them on long term.

---

#### **SNOWBIKE TOW-STRAP HOOK UP:**

1. Use the 74" leads on the machine that is doing the towing. Loop them onto the snowbike frame just behind the drive system or hook them on to each of the factory foot pegs (hooking them to the frame works better). Guide the end through the rear bumper to keep them centered. Install a carabiner to hook them together at the ends.
2. Use the 44" leads on the machine getting towed. Hook them onto each of the factory foot pegs. Guide them around the frame and in-between the fork tubes. Install a carabiner to hook them together at the ends.
3. Use the carabiners to connect the 15' tow lead to each machine. Begin Towing.

#### **SNOWMOBILE TOW-STRAP HOOK UP:**

1. Use the 74" leads on the machine that is doing the towing. Loop them onto the back of the running board to its strongest point. Guide the end through the rear bumper to keep them centered. Install a carabiner to hook them together at the ends.
2. Use the 44" leads on the machine getting towed. Loop them onto each A-arm or to the ski loops. Install a carabiner to hook them together at the ends.
3. Use the carabiners to connect the 15' tow lead to each machine. Begin Towing.

