

| | |
|-------------------------------|-----------------------|
| Product Name: | Bluelab pH Pen |
| Product Code: | PENPH |
| UPC Code: | 9421024920234 |
| Country of Origin: | New Zealand |
| Tariff Code: | 9027.80 |
| Shipping Quantity: | Sold as singular unit |
| Packaging Information: | |
| Packaged Weight: | 0.24 kg / 0.529lb |
| Packaged Length: | 205 mm / 8.07 in |
| Packaged Width: | 94 mm / 3.70 in |
| Packaged Height: | 48 mm / 1.80 in |

Sales Description:

NOTE: this copy can be used in brochures, catalogues or online

The ultimate handy solution for measuring pH

Perfect for quick and easy pH and temperature readings direct from your solution. The Bluelab® pH Pen is the preferred option for hand held pH meters. It provides a compact, quick and handy way to manage the success of your crops to ensure maximum uptake of nutrients.

A key parameter that affects nutrient uptake is whether your solution is acid or alkaline. We measure this in pH. Teamed with our Bluelab® Conductivity Pen you have a robust, convenient and accurate measurement system.

Register your product here: <http://bluelab.com/product-registration>

Features:

- Measures pH and temperature
- Selectable units for temperature
- Fully waterproof
- Backlit LCD display
- Double junction probe (not replaceable)
- Simple two point calibration process with 30 day calibration indicator
- Hold reading function
- Low battery indicator
- Auto off function
- Automatic temperature compensation
- 1 AAA replaceable battery included

Product Guarantee:

One year free repair or replacement guarantee.


Product Image:

Product images available for Screen or Web use:

- Bluelab-pHPen-F-capoff-MR-flat-RGB.jpg
- Bluelab-pHPen-F-capoff-WEB.jpg
- Bluelab-pHPen-F-capoff-WEB-sml.jpg
- Bluelab-pHPen-C-MR-Flat-RGB.jpg
- Bluelab-pHPen-C-WEB-Lrg.jpg
- Bluelab-pHPen-C-WEB-sml.jpg

Product images available for PRINT:

Note: these images are high resolution in CMYK.

- Bluelab-pHPen-C-MR-flat-CMYK.tif
- Bluelab-pHPen-F-capoff-MR-flat-CMYK.tif

Technical Specifications:

| | |
|--|--|
| Measurement Range: | 0.0 – 14.0 pH 0 – 50 °C / 32 – 122 °F |
| Resolution: | 0.1 pH 1 °C / 1 °F |
| Accuracy at 25°C / 77°F: | ± 0.1 pH, ± 1 °C / ± 2 °F |
| Automatic Temperature Compensation: | Yes |
| Operating Environment: | 0 – 50 °C / 32 – 122 °F |
| Calibration: | Two point, pH 7.0 & pH 4.0 or pH 10.0 |
| Power Source: | 1 x AAA alkaline battery |
| User Manual Languages Available: | English; Español-España; Español-Latinoamérica; Français; Français-Canada; Nederlands; Deutsch |
| Certifications: | CE and FCC |