SHOWER / FAUCET / ACCESSORIES

BATHROOM

COMPLETE HARDWARE IS THE CORNERSTONE OF HIGH QUALITY

MUTE TECHNOLOGY 🔊

When it comes to mute technology, we are undoubtedly in a better position. Whether it is the smooth wall of the tap cavity. The bubbler has seven layers of filtering, which can save water, reduce noise and prevent splashing. The filter screen of the valve element, silencing treatment, etc. are all just right and meticulous.

SMOOTH TECHNOLOGY

Speaking of smooth operation, our unique valve element is made of advanced ceramic alloy in a tightly closed environment, and is coated with a special lubricating coating. At the same time, the special oil tank design on the surface of the ceramic chip makes your faucet smooth for many years. Therefore, the smooth technology ensures that the product can maintain a comfortable and reliable performance during its service life without any maintenance. At the same time, the large operation rotation angle means that the cold and hot adjustment process of water temperature is smooth, gradual and accurate.

FLOW TECHNOLOGY

We pay attention to the precious water resources and at the same time let you enjoy your bath. Whether it is the seven layer filtering of the bubbler or the aerated constant flow device of the shower. In general, the higher the water pressure of the bubbler, the greater the flow. Even when the water pressure of our washbasin and kitchen faucet is above 0.3MPa, the flow of our special bubbler is constant. This constant current technology has been widely recognized and respected by the industry.



CUT OFF THE NOZZLE

GRAVITY CASTING



CNC MACHINING

POLISHING



CASTING BLANK



PRECISION CNC LATHE



IUSTALLATION GUIDE



1、参考支架的开孔位置尺寸,尺子垂线定位,选用直径9.5mm~10mm钻头, 开孔深度≈50mm,然后敲入膨胀缓丝套。 Refer the size of frame, positioning, drilling the wall hole in 2. Screw on the expansion screw, screw the nut with 10 mm Screw the nut with wrench around 50 mm with 9.5-10mm drill.



-Surface finished : Mirror and Brushed

Three kinds of air outlet mode 1.Big size of rainfall

like having the bath in the nature 2. Mist spraying mode

Recommend collocation program:

Concealed multifunctional controller BAX401X

APPLICATION INSTRUCTION

The correct way of connecting the overhead shower

following electrical connection graphical representation)

the bathroom

3. Bubble massage mode

Flush the nine system

Surface condition

Electrical connection

electrician) Lamplight switch

suitable for the roof shower head

-with colorful LED light, can be changed by power control

420x270, The best outlet position , combined the air and water together , let you feel

4 x 2L spray, the Atomization come out evenly, give you a romantic atmosphere in

New type of bubble massage mode bring you an unexpected shower feeling, Using

In order to combine the beautiful water outlet and the functional control perfectly,

Wash both of the cold and hot water supply pipes after finishing installed the whole system

Pls make sure the points below before you are ready to install the head :All fasten surfaces must be smooth (no salient or protruding ceramic)and contains no flaw , and pls be sure the wall structure in

Preinstallation service cable: 230V/N/PE/50Pz (Electrical connection must be handled by professional

Must be installed out of the shower range or connected with the ceiling light together. (Refer to the

the certificated silica gel nozzle, easy to clean and keep the water pure

we advise you to use the high flow capacity multifunctional control valve.

This overhead shower is only allowed to be connected with the diverter valve

2、旋上膨胀螺杆,用10mm扳手收紧螺母至合适力度。 crew, screw the nut with 10 mm wrench



3、支架缺口翻外學入,用螺母收至合适的高度(此高度为活动尺寸,视天花板 安装的尺寸高度调节)保证每个支架的高度一致。 Outward the notch, install the bracket, adjust the height. (the height could be flexible, depends on the ceiling) keep all bracket in same level



4、将花游拍起挂入支架的空全挂钩(清注音语保已挂语)向上挂起另外一张到 支架螺丝的位置,前面接开支架两边的总带,将握杜卡入支架孔中,用M4摆母 固定牢固。然后将将你的整理公监的上支架固定牢固。 4、Hang the shower to the hock of bracket. (insure the shower is stable), push up the other side up to the bracket, adjust the pothook hang the screw to bracket, fixed with M4 screw. (ock the rest nuts.



连接水管到花洒,安灵后试水,必须确保管道没有渗漏(连接前必须将管 通进行预冲洗,避免管道场意)。
 Connect the pipe to the shower, leaking test, insure not any leaking (for avoid clogging, it must be flushing before connect the pipe)



6. (注意此工序需要两个劳动力) 御上手套将面嵌孔位对油喷嘴推上,用4mm 式和銀行上螺丝(注意面板因天石板平齐即可,不必近于用力锁紧), 6. conderTins process requires teom and), with gives, Push up the panel accord the nozzles, lighten the screw with 4mm Allen key(keep the panel in same level with ceiling)

ADORN THE ELEGANT BATH FOR YOU. USE HIGH STANDARD SHOWER HEAD PRODUCTS.







空气式雨淋 🔲 🌢 Raingair

喷雾 Mist spraying





Water fall

Raing air and Water fall













喷雾 + 气泡式按摩 Mist spraying and Bubble massage

空气式雨淋+喷雾 Raing air and Mist spraying











SSW271-LED 680X430 27"Stainless steel shower head



SSW272-LED

680X430









						6											1
	 					÷									- F	٦.	
	 					٠											
	 					٠											
	 	٠	٠			٠											
	 		٠		٠	٠		٠	٠		٠	٠	٠				0
	 	٠		٠	٠			٠		٠	٠		٠		- 1		430
-++	 	-	-		-	•	-	•	-		-	-	-	•			+ +
	 		•			Ŧ		٠	•		٠	•					1 1
	 • •					٠											
	 • •	٠	٠	-	•	٠	•	٠	٠	٠	•	٠	٠	•			
	 • •	•	٠	٠	٠		٠	٠	٠	٠	٠	٠	٠	•			
	 • •							٠		•	•			•			
	 • •		٠	٠	٠		٠	٠	٠	٠	٠	٠	٠	•	- L		







27"Stainless steel shower head





SSW274-LED 680X430 27"Stainless steel shower head



G1/2



SSW	241				
600) 24"S		ess ste	eel sł	nower he	ad
T		$\overline{}$			

1	-	-							50									-
-									i									
									٤.									
			٠						٤.	٠			٠					
					٠				٠	٠	٠		٠	٠		٠		
			٠	٠	٠		٠		÷		٠		٠	٠		٠		
C			-		٠	٠			ŧ٠		٠	٠	٠			٠	-	
1 00			٠			٠			±.,	٠		٠		٠	٠	٠		
			•	•	•	•		-	۰	-	•	•	•	•	•	•	-	+
430		•	٠	٠	٠	٠	•		t i	٠	٠	٠	٠	٠	٠	٠	•	
		•	٠	٠	٠	٠	٠		t :	٠	٠	٠	٠	٠	٠	٠	•	
		•				-			t :	•	-		•	-	-	-		
		•							t :			*						
									2.1		-							
				-		-			τ.	•	-	-		-	-	•		
			. 4															

SSW242
600X430 24"Stainless steel shower
24 Stainless steel snower













r head

前面弧度

采用不锈钢材质。极致的工艺,超凡的质感,时尚的R角曲线, 过渡光亮细致,独有的前弧设计,给你非凡的浴室体验,每看 一眼都触动心灵。

Front curve

SS304 material, exquisite workmanship, extraordinary touch, fashion R curve, excellent jointing. Unique front curve design, bring you the extraordinary bath experience. Touch your soul in every sign.





F

.

H

AVAILABLE NIPPLE EU patent licence:002704734-0002 Material:Stainless steel

Maximum sway angle:19° Available function: Air function













SRS121 Ø300X7 12" Stainless steel shower head





SRS161 Ø400X7 16" Stainless steel shower head









-.

AVAILABLE NIPPLE EU patent licence:002704734-0005 Material:Stainless steel Maximum sway angle:19° Available function:Air function

可提供颜色处理 Available colour



001 Series











AVAILABLE NIPPLE H





300X200

001 Series





G1/2 300×200

SSR122 300X200X7 12" Stainless steel shower head





SHOWER COLOR





BLACK

From idea to design, from material to manufacturing, every product is essence of creation through continuous denial to get the best and satisfactory version, every design is perfect - proofing artwork not only just for quality.

Complying with the memands of the time constantly the brand and idea have already incorporated the beautiful and practical element, thus press close to the life of city people even more.



1. 极致的工艺,时尚的 R 角曲线,质感超凡。 Acme process,fashion R curve line,makes imposing to behold.



2. 雨淋式喷洒模式 200×160 出水范围 Rainfall Outlet range :200*160



 瀑布式喷洒模式 大出水量的瀑布式出水嘴
 Waterfall Big water yield of the waterfall spout

001 Series



CHROME









3. HT012 手持花洒 Fashion designed hand shower 6.G101银灰软管 Silvery grey shower hose



CONCEALED SHOWER SET

暗装淋浴套装

多功能淋浴花洒 MULTIFUNCTIONAL SHOWER HEAD BSZ223 (11170200411)

产品尺寸: 550×230×55 - 可做镀铬黄铜前壳和珍珠白高光烤漆处理

两种出水模式: 1. 雨淋式喷洒模式 200×160 出水范围 2. 瀑布式喷洒模式 大出水量的瀑布式出水嘴

配合易清洁认证硅胶雨淋水嘴,拨动快洁。

喷水伸出尺寸 在规划中,请考虑淋浴房的尺寸和布局及两种喷水模式的喷水角度。

Size:550x230x55 Surface finished: Chrome and White (According to your mind)

Two functions : 1. Rainfall Outlet range :200*160 2: Waterfall Big water yield of the waterfall spout

Use certificated silica gel nozzle, easy to clean

The size of spray outlet Please consider shower room size, spatial position of two functions in your building planning.











BA311

G101 0 Hose

001 Series

......



Concealed shower mixer









Ô

BA312 Concealed shower mixer

BSZ221 550X230X55 22"Bass shower head

HT007 25X15X200 Hand shower

CZ003 Holder

BA314T Diverter

CZ005 Spout

G205 Hose

16



て 瀑布式 WATERFALL

宽大而浑厚的瀑布冲落在疲惫的双肩、酸胀的腰背,紧张疲 劳的肌肉得以最大限度的舒缓,压力得以最大的释放那该是 多么享受的一件事。

You should not afraid of cold weather in the winter in the bathroom , because it can help you shower and wash your hair in the same time.



SSZ226 550X170X30 22"Stainless steel shower head











23

SSZ227 550X170X30 22"Stainless steel shower head







SRZ225 SRZ224 550X230X2 20°Stainless steel shower head

 $\overline{}$





BSZ221 550X230X23 22"Bass shower head











Every line, every angle, every combination is a masterpiece of wisdom. Excellent quality and humanized design, feel high-end quality and elegant taste through details.

TWO WATER OUTLET MODES OF HANDSHOWER









001 Series

MAN Sorios







TN8888 Single lever basin mixer Chrome

PRODUCT PARAMETERS:

- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,

EPDM internal management and insurance company underwriting;







TN8888







PRODUCT BREAKDOWN















Tonal harmonious collocation, the contrast of administrative levels is trendible, 100 changeful expression form, maintained the neat and fluent of whole space completely, smooth feeling ilumines a person.



PRODUCT BREAKDOWN













MAN Series





PRODUCT BREAKDOWN



















DIGITAL DISPLAY SHOWER



Rotating water outlet design, flexible and convenient to use

PRODUCT **BREAKDOWN**











PRODUCT BREAKDOWN





-

Single lever basin mixer Chrome



1

TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome







TN8888 Single lever basin mixer Chrome

E



-

001 Series



TN8888



















PRODUCT BREAKDOWN















无需特殊工具即可拆卸更换阀芯方便快捷









TN8888

Single lever basin mixer Chrome





- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,

EPDM internal management and insurance company underwriting;















MAN Sories







TN8888 Single lever basin mixer Chrome







TN8888 Single lever basin mixer Chrome







TN8888 Single lever basin mixer Chrome





TN8888 Single lever basin mixer Chrome











TN8888 Single lever basin mixe Chrome





TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome



PRODUCT PARAMETERS:

- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,

EPDM internal management and insurance company underwriting;



 Image: Single lever basin mixer Chrome







Single lever basin mixer Chrome J^L J^L J^L









TN8888

Chrome

Single lever basin mixer

012-1-1 022X1.0-

×+0-

TN8888 Single lever basin mixer Chrome

TN8888 Single lever basin mixer Chrome

h.

TN8888

Chrome

Single lever basin mixer





TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome



Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome







TN8888 Single lever basin mixer Chrome

TN8888 Single lever basin mixer Chrome





TN8888 Single lever basin mixer





Single lever basin mixer Chrome

Chrome







TN8888 Single lever basin mixer Chrome

TN8888 Single lever basin mixer Chrome



41

TN8888

TN8888

Chrome

Single lever basin mixer



TN8888 Single lever basin mixer Chrome



Single lever basin mixer Chrome

TN8888 Single lever basin mixer Chrome













TN8888









Single lever basin mixer Chrome

Chrome





TN8888

Single lever basin mixer













TN8888 Single lever basin mixer Chrome

TN8888 Single lever basin mixer Chrome









TN8888 Single lever basin mixer Chrome

TN8888 Single lever basin mixer Chrome







TN8888 Single lever basin mixer Chrome

TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome

OCO DATE Black Output Connect Output Date Black



TN8888 Single lever basin mixer Chrome

PRODUCT PARAMETERS:

1. Gravity casting, using national standard 59A brass;

3. Standard high precision ceramic valve core and copper gland; 4. Thickened stainless steel tooth tube, open copper mounting nut;

EPDM internal management and insurance company underwriting;

2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;

5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,

1 77



















TN8888

Single lever basin mixer Chrome



PRODUCT PARAMETERS:

- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,

EPDM internal management and insurance company underwriting;











TN8888

Single lever basin mixer Chrome

PRODUCT PARAMETERS:

- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,

EPDM internal management and insurance company underwriting;

















TN8888 Single lever basin mixer Chrome



PRODUCT PARAMETERS:

- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,
- EPDM internal management and insurance company underwriting;















TN8888

Single lever basin mixer Chrome

PRODUCT PARAMETERS:

- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,
- EPDM internal management and insurance company underwriting;





Chrome Matte Black Brushed Gurnetal Brushed Gold-2r



TN8888

Single lever basin mixer Chrome

PRODUCT PARAMETERS:

- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,

EPDM internal management and insurance company underwriting;







TN8888 Single lever basin mixer Chrome

er





TN8888 Single lever basin mixer Chrome $\mathbf{F} \mathbf{F}$













TN8888 Single lever basin mixer Chrome





TN8888 Single lever basin mixer Chrome



PRODUCT PARAMETERS:

TN8888

- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,
- EPDM internal management and insurance company underwriting;













TN8888 Single lever basin mixer Chrome TN8888 Single lever basin mixer Chrome

001 Series



The fresh design style is as simple as nature, and every detail is interpreted incisively and vividly with a unique aesthetic concept.We have always used art to think about the deeper aspects of life. While being artistic, it can reflect more human care.



TN8888

Single lever basin mixer Chrome

PRODUCT PARAMETERS:

- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,

EPDM internal management and insurance company underwriting;





TN8888 Single lever basin mixer Chrome 

TN8888 Single lever basin mixer Chrome TTTT









7777



TN8888 Single lever basin mixer Chrome



TN8888

Single lever basin mixer Chrome



- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,

EPDM internal management and insurance company underwriting;



TN8888 Single lever basin mixer Chrome

空位



TN8888



TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome



TN8888

Single lever basin mixer Chrome

PRODUCT PARAMETERS:

1. Gravity casting, using national standard 59A brass;

3. Standard high precision ceramic valve core and copper gland;

4. Thickened stainless steel tooth tube, open copper mounting nut;

EPDM internal management and insurance company underwriting;

2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;

5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,











TN8888 Single lever basin mixer Chrome









MORE SIZE MORE CHOICE

ine workmanship can present fine works of art, integrate art and life to the greatest extent, advocate a new living experience, and seek a balance between function and aesthetics.Add an irresistible charm to your home space.











TN8888 Single lever basin mixer Chrome







μ

TN8888 Single lever basin mixer Chrome



001 Series







TN8888 Single lever basin mixer Chrome







PRODUCT PARAMETERS:

- 1. Gravity casting, using national standard 59A brass;
- 2. The surface is thickened and plated 9-10um, passing the 24h acid salt spray test;
- 3. Standard high precision ceramic valve core and copper gland;
- 4. Thickened stainless steel tooth tube, open copper mounting nut;
- 5. The inlet pipe is 60cm long, copper joint, 304 stainless steel braided outer pipe,

EPDM internal management and insurance company underwriting;



TN8888 Single lever basin mixer Chrome











We continue to innovate in design and create a cutting-edge bathroom fashion that meets the needs of contemporary users. The meticulous appearance, function and structure design allows people to focus on the emotional experience in the bathroom and enjoy comfort and convenience.



1

TN8888 Single lever basin mixer Chrome



N



TN8888 Single lever basin mixer Chrome



AAA



TN8888 Single lever basin mixer Chrome











TN8888 Single lever basin mixer Chrome







TN8888 Single lever basin mixer Chrome



]



TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome

TN8888

Single lever basin mixer Chrome



TN8888

Single lever basin mixer Chrome





TN8888



TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome



TN8888 Single lever basin mixer Chrome

















TN8888 Single lever basin mixer Chrome







TN8888 Single lever basin mixer Chrome













TN8888 Single lever basin mixer Chrome













TN8888

Single lever basin mixer Chrome











TN8888







% <u>500/600</u>



TN8888 Single lever basin mixer Chrome





TN8888 Single lever basin mixer Chrome









TN8888 Single lever basin mixer Chrome











26	6	400/500	
122			











001 Series



TN8888 Single lever basin mixer Chrome





TN8888 Single lever basin mixer Chrome











TN8888 Single lever basin mixer Chrome







88888

88888

88888

88888





TN8888 Single lever basin mixer Chrome





TN8888 Single lever basin mixer Chrome

001 Series

