



Cascade Stainless Solutions 2 Head Keg Washer – Session Line (Economical Options)

<https://cascade-stainless.com>

info@cascade-stainless.com

+1-541-640-3210

- 7-inch Allen-Bradley Touchscreen HMI
- Allen-Bradley Micro 820 PLC and electrical components
- Automatic Wash Cycle Sequence | “Set and Forget” Operation
- 26 Kegs Per Hour with Factory Settings
- Fully-Adjustable Keg Washing Cycle Set Points and Parameters
- Digital Temperature and Pressure Read-Outs
- 3/4HP AMT Pump
- Spear-cleaning functionality
- CO2 Keg Pressurization to User Determined Set-point
- Air and CO2 Purge Cycles
- Brewer-Friendly Interchangeable Tri-Clamp Valves and Fittings
- stainless steel pneumatic valves
- 304 Stainless Steel Frame
- Heavy Duty Lockable Casters
- 30-gallon Stainless Steel Sanitizer Reservoir - Recirculated or Drained
- 30-gallon Stainless Steel Hot Caustic Reservoir
- 5500W Stainless Steel Heating Element
- Micro Matic Stainless Steel Keg Couplers
- Dimensions 2-Head: 53” L x 45” W x 48” H
- Air Requirements 120 PSI @ 10 SCFM
- Recommended Water Requirements: 3/4" Line at 50 PSI equaling ~ 10 GPM
- Drain Requirement: No less than 1" ID drain hose
- Power Requirements Single or 3 Phase 240V 30 Amp
- Built in the USA - 1 Year Warranty