



Corotop FLEX

Single-sided tape with aluminium

The polypropylene single-sided adhesive tape covered with aluminium. It protects against moisture and solvent penetration. It is resistant to UV-rays and ageing processes.



Advantages

- ✓ good adherence properties
- ✓ isolates vapour and moisture
- ✓ universal – to be used on both smooth and rough surfaces

Application

- ✓ for bonding aluminium foils
- ✓ for fixing damages in aluminium foils
- ✓ as bonding element in ventilating, air-conditioning and heating systems

Characteristics

Material	PP, aluminium, acrylic adhesive	Resistance to breaking	100 N/25 mm
Colour	silver	Elongation to break	140 %
Length	50 m	Adhesion to steel	5 N/25 mm
Width	50 / 75 mm	Temperature resistance	+10°C to +80°C
Thickness	0,051 mm		

Installation

- 1 Clean the surface from dust and other contamination.
2. Do not tighten the tape on the bonding surface.
3. Observe the recommended temperature for using.

Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in covered means of transport, secured against damage.

Packaging

Quantity per box (pcs.):	36 (50mm) 24 (75mm)
Quantity on a pallet (box./pcs):	72 / 2592 (50mm) 72 / 1728 (75mm)

The information contained in this data sheet, particularly recommendations regarding the manner and conditions of application as well as the scope of use of the product, have been developed based on our experience, our best knowledge and in good faith. Apart from the information given in this data sheet, health and safety regulations, etc. must be observed. This technical data sheet supersedes all previous versions applicable to this product.