

Corotop PUR

Sealing Tape

A self-adhesive sealing tape in the form of cross-linked polyethylene foam with closed cell structure. Designed for sealing the contact points between the roof membrane and counter-battens and roof truss. It eliminates irregularities between the counter-battens, roof membrane and rafters. It is characterised by high thermal insulation.



Advantages

- ✓ good adhesion to smooth and porous surfaces
- ✓ weatherproof
- ✓ prevents water from penetrating the thermal insulation, at the membrane penetration points

Application

- ✓ for sealing the contact points between the roof membrane and counter-battens and roof truss

Parameters

Material	polyethylene	Relative elongation at rupture	≥ 9 %
Colour	grey	Apparent density	≥ 55 (kg/m ³)
Thickness	3 mm	Temperature of application	from +5 to +40 °C
Width	40 / 50 / 60 mm	Temperature resistance	from -30 to +100 °C
Length	30 m		
Tensile strength	≥ 740 (kPa)		

The product has passed a positive assessment of its performance for the intended use: ventilation and roofing. Confirmation document: National Technical Assessment No. ITB-KOT-2020/1462 edition 1.

Installation tips

1. Clean the surface from dust and other contamination.
2. Apply the sealing tape to the counter-battens on the side that will stick to the membrane in such a way that the whole surface of the tape covers the counter-battens
3. Nail the counter-battens to the rafters along the fixing points of the rafters, so that each puncture point of the foil is sealed with the tape.

Storage

The product should be stored in the manufacturer's original packaging, in dry, covered areas. The product should be transported in covered means of transport, secured against damage.

Packing

Quantity per packaging [pcs.]:	12 / 18 / 16
Quantity per palette [pcs.]:	252 / 216 / 192