DesignLights Consortium





Classification	Premium
Primary Use	Architectural Flood and Spot Luminaires
Reported Input Wattage	47.6 W
Reported Light Output	5765 lm
Reported CCT	4500 K
Reported CRI (Ra)	80
Product ID	PVAAHIP9
DLC Family Code	GGGGRR
Listing Status	Listed
Date Qualified	2019-12-27

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PVAAHIP9
Manufacturer	Atlas Lighting Products
Brand	Atlas Lighting Products, Inc.
Model Number	FS6L45K [BLANK, PC, PM, WT, BK, T]
Parent	No
Classification	Premium
DLC Family Code	GGGGRR
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	Mid Output	
Primary Use Designation	Architectural Flood and Spot Luminaires	

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Exterior Photocell
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5765 lm
Reported Efficacy (AC)	121.05 lm/W
Reported CCT	4500 K
Reported CRI (Ra)	80
Reported R9	27
Reported IES Rf	86
Reported IES Rg	98
Reported IES Rcs,h1	-10
Reported Default Light Output	5765 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Default Input Wattage Voltage Range	120-277 V
Papartad Dafault Input Wattage	47.6 W
Reported Maximum Input Wattage	47.6
Reported Power Factor	0.968
Reported Total Harmonic Distortion	8.7 %
Reported Input Wattage	47.6 W

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

|--|

VERSION HISTORY VIEW DETAILS

2022-05-19	Listed	5.1	Premium
2020-03-30	Listed	5	Premium

2019-12-27	Listed	4.4	Premium
		** *	