

# DesignLights Consortium



Classification	Standard
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	238.9 W
Reported Light Output	33935 lm
Reported CCT	4500 K
Reported CRI (Ra)	80
Product ID	PTMBL480
DLC Family Code	<a href="#">HHHDBV</a>
Listing Status	Listed
Date Qualified	2017-09-14

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PTMBL480
Manufacturer	Atlas Lighting Products
Brand	Atlas Lighting Products, Inc.
Model Number	ILH436LL [OPTIONS]
Parent	No
Classification	Standard
DLC Family Code	HHHDBV
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	High-Bay
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings

## CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	33935 lm
Reported Efficacy (AC)	142 lm/W
Reported CCT	4500 K
Reported CRI (Ra)	80
Reported R9	6
Reported IES Rf	83
Reported IES Rg	95
Reported IES Rcs,h1	-12
Reported Default Light Output	33935 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	238.9 W
Reported Total Harmonic Distortion	9.47 %
Reported Power Factor	0.981
Reported Default Input Wattage	238.9 W
Voltage Range	120-480 V

## VERSION HISTORY VIEW DETAILS

2021-08-05	Listed	5.1	Standard
2020-03-30	Listed	5	Premium
2019-01-07	Listed	4.4	Premium
2018-11-02	Listed	4.4	Premium
2018-05-02	Listed	4.3	Premium
2017-09-14	Listed	4.2	Premium