# **DesignLights Consortium**





Classification	Standard
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	306.2 W
Reported Light Output	42009 lm
Reported CCT	4500 K
Reported CRI (Ra)	80
Product ID	PA6Y6JB4
DLC Family Code	HHHDBV
Listing Status	Listed
Date Qualified	2016-10-14

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PA6Y6JB4
Manufacturer	Atlas Lighting Products
Brand	Atlas Lighting Products, Inc.
Model Number	ILH448LL [OPTIONS]
Parent	No
Classification	Standard
DLC Family Code	HHHDBV
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	High-Bay
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings

# **CONTROL FEATURES VIEW DETAILS**

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability  Sensor Type  Occupancy Sensing  SSL V5 Wired Communication Protocol  SSL V5 Wireless Communication Protocol  No Wireless Protocol  Field Adjustable Light Output  No  White-Tunable  No  Warm-Dimming  No  Field Adjustable Light Distribution  No		
SSL V5 Wired Communication Protocol  SSL V5 Wireless Communication Protocol  Field Adjustable Light Output  No  White-Tunable  No  Warm-Dimming  No	Integral Control Capability	No Control Capability
SSL V5 Wireless Communication Protocol No Wireless Protocol  Field Adjustable Light Output No  White-Tunable No  Warm-Dimming No	Sensor Type	Occupancy Sensing
Field Adjustable Light Output  White-Tunable  Warm-Dimming  No	SSL V5 Wired Communication Protocol	0-10V Analog
White-Tunable No Warm-Dimming No	SSL V5 Wireless Communication Protocol	No Wireless Protocol
Warm-Dimming No	Field Adjustable Light Output	No
	White-Tunable	No
Field Adjustable Light Distribution No	Warm-Dimming	No
	Field Adjustable Light Distribution	No

# REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	42009 lm
Reported Efficacy (AC)	137 lm/W
Reported CCT	4500 K
Reported CRI (Ra)	80
Reported R9	6
Reported IES Rf	83
Reported IES Rg	95
Reported IES Rcs,h1	-12
Reported Default Light Output	42009 lm

#### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	306.2 W
Reported Total Harmonic Distortion	9.74 %
Reported Power Factor	0.983
Reported Default Input Wattage	306.2 W
Voltage Range	120-480 V

## **VERSION HISTORY VIEW DETAILS**

2021-08-05	Listed	5.1	Standard
2020-03-30	Listed	5	Premium
2019-01-07	Listed	4.4	Premium
2018-11-02	Listed	4.4	Premium
2018-05-02	Listed	4.3	Premium
2017-09-07	Listed	4.2	Premium
2017-08-11	Listed	4.2	Premium
2017-04-28	Listed	4.2	Standard
2017-04-01	Listed	4.1	Standard

2016-10-14 Listed 4 Standard	2010-10-14		4	Standard
------------------------------	------------	--	---	----------