

DesignLights Consortium



Classification	Standard
Primary Use	Outdoor Full-Cutoff Wall-Mounted Area Luminaires
Reported Input Wattage	37.74 W
Reported Light Output	4130 lm
Reported CCT	4500 K
Reported CRI (Ra)	70
Product ID	P894U7BK
DLC Family Code	PPPREZ
Listing Status	Listed
Date Qualified	2016-08-11

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	P894U7BK
Manufacturer	Atlas Lighting Products
Brand	Atlas Lighting Products, Inc.
Model Number	WSPS40LED [BLANK, PC, PM, WT, BK, SP]
Parent	No
Classification	Standard
DLC Family Code	PPPREZ
Input Power Type	AC
Notes	Product Updated on 12/21/2020

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Low Output
Primary Use Designation	Outdoor Full-Cutoff Wall-Mounted Area Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Sensor Type	Exterior Photocell
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4130 lm
Reported Efficacy (AC)	109.44 lm/W
Reported CCT	4500 K
Reported CRI (Ra)	70
Reported R9	-38.1
Reported IES Rf	75
Reported IES Rg	93
Reported IES Rcs,h1	-18
Reported Default Light Output	4130 lm
Reported BUG Rating	B1 U0 G1

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	37.74 W
Reported Total Harmonic Distortion	5.18 %
Reported Power Factor	0.977
Reported Default Input Wattage	37.74 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2020-12-21	Listed	5.1	Standard
2018-11-02	Delisted	4.4	Standard
2018-05-02	Listed	4.3	Standard
2017-04-28	Listed	4.2	Standard
2017-04-01	Listed	4.1	Standard
2016-08-11	Listed	4	Standard