

# DesignLights Consortium



Classification	Premium
Primary Use	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	45 W
Reported Light Output	5625 lm
Reported CCT	3500 K
Reported CRI (Ra)	82
Product ID	S-X7C2MV
DLC Family Code	<a href="#">UUUVBR</a>
Listing Status	Listed
Date Qualified	2022-11-08

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-X7C2MV
Manufacturer	ESL Vision
Brand	ESL
Model Number	ESL-CSS-830-24-3445W-3550K
Parent	Yes
Classification	Premium
DLC Family Code	UUUVBR
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces

## CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Daylight Sensing,Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5625 lm
Reported Efficacy (AC)	125 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	7
Reported IES Rf	80
Reported IES Rg	90
Reported IES Rcs,h1	-12
Reported Minimum Light Output	4522 lm
Reported Maximum Light Output	5715 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	5625 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	45 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	34 W
Reported Maximum Input Wattage	45
Reported Default Input Wattage	45 W
Voltage Range	120-277 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	5478 lm
Tested Efficacy (AC)	126.3 lm/W

Tested CCT	3438 K
Tested CRI (Ra)	83
Tested R9	7
Tested IES Rf	83
Tested IES Rg	93
Tested IES Rcs,h1	-12 %
Tested Duv	0.0014

## TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	43.4 W
Tested Total Harmonic Distortion	12.5 %
Tested Power Factor	0.959

## VERSION HISTORY VIEW DETAILS

2022-11-08	Listed	5.1	Premium
------------	--------	-----	---------