# **DesignLights Consortium**





| Classification         | Premium   |
|------------------------|---|
| Primary Use            | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 136.3 W   |
| Reported Light Output  | 22081 lm  |
| Reported CCT           | 5000 K  |
| Reported CRI (Ra)      | 80  |
| Product ID             | S-7CADOS  |
| DLC Family Code        | ZZZFOV  |
| Listing Status         | Listed  |
| Date Qualified         | 2022-12-08  |

# **PRODUCT INFORMATION VIEW DETAILS**

| Qualified Product List         | Solid State Lighting   |
|--------------------------------|--|
| Technical Requirements Version | 5.1  |
| Product ID                     | S-7CADOS   |
| Manufacturer                   | ESL Vision   |
| Brand                          | ESL Vision   |
| Model Number                   | ESL-ERHB-135W-150-XX-90D(XX can be any letter)-[ALL MOUNTING OPTION] |
| Parent                         | No   |
| Classification                 | Premium  |
| DLC Family Code                | ZZZFOV   |
| Input Power Type               | AC   |

### PRODUCT CATEGORIZATION VIEW DETAILS

| Category Indoor Luminaires |   |
|----------------------------|---|
| General Application        | High-Bay  |
| Primary Use Designation    | High-Bay Luminaires for Commercial and Industrial Buildings |

# **CONTROL FEATURES VIEW DETAILS**

| Integral Controls                      | No                                 |
|--|------------------------------------|
| Dimming Capability and Range           | Continuous Dimming to 10% or below |
| Integral Control Capability            | No Control Capability              |
| Sensor Type                            | No Sensor                          |
| SSL V5 Wired Communication Protocol    | 0-10V Analog                       |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol               |
| Field Adjustable Light Output          | No                                 |
| White-Tunable                          | No                                 |
| Warm-Dimming                           | No                                 |
| Field Adjustable Light Distribution    | Yes                                |
| Field Adjustable Distribution Type     | Integral FALD                      |

# REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 22081 lm    |
|-------------------------------|-------------|
| Reported Efficacy (AC)        | 162.02 lm/W |
| Reported CCT                  | 5000 K      |
| Reported CRI (Ra)             | 80          |
| Reported R9                   | 1           |
| Reported IES Rf               | 83          |
| Reported IES Rg               | 94          |
| Reported IES Rcs,h1           | -13         |
| Reported Default Light Output | 22081 lm    |

### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 136.3 W   |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 %      |
| Reported Power Factor              | 0.9       |
| Reported Maximum Input Wattage     | 135       |
| Reported Default Input Wattage     | 135 W     |
| Voltage Range                      | 120-277 V |

### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

|--|--|--|--|--|

### PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

| SPDX File | Download File |  |
|-----------|---------------|--|
|-----------|---------------|--|

# **VERSION HISTORY VIEW DETAILS**

| 2022-12-08 Listed 5.1 Premium |  |
|-------------------------------|--|
|-------------------------------|--|