DesignLights Consortium





Classification	Standard
Primary Use	Retrofit Kits for Fuel Pump Canopy Luminaires
Reported Input Wattage	104.8 W
Reported Light Output	13576 lm
Reported CCT	4000 K
Reported CRI (Ra)	83
Product ID	PQ2HQL77
DLC Family Code	HHHCWC
Listing Status	Listed
Date Qualified	2020-03-30

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PQ2HQL77
Manufacturer	ESL Vision
Brand	ESL Vision
Model Number	ESL-MUR-105W-340
Parent	No
Classification	Standard
DLC Family Code	HHHCWC
Input Power Type	AC
Notes	Product Updated 7/27/2022

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Retrofit Kit	
General Application	High Output	
Primary Use Designation	Retrofit Kits for Fuel Pump Canopy Luminaires	

CONTROL FEATURES VIEW DETAILS

Dimming Capability and Range	Continuous Dimming to 10% or below		
Integral Control Capability	No Control Capability		
Sensor Type	Exterior Photocell,Occupancy Sensing		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	No		
White-Tunable	No		
Warm-Dimming	No		
Field Adjustable Light Distribution	No		

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	13576 lm
Reported Efficacy (AC)	129.54 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	83
Reported R9	11
Reported IES Rf	83
Reported IES Rg	94
Reported IES Rcs,h1	-13
Reported Default Light Output	13576 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	104.8 W
Reported Total Harmonic Distortion	15.8 %
Reported Power Factor	0.917
Reported Default Input Wattage	104.8 W
Voltage Range	120-277 V

LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose
--	-----------------

VERSION HISTORY VIEW DETAILS

2022-07-27	Listed	5.1	Standard
2022-06-30	Delisted	5	Standard
2020-03-30	Listed	5	Standard
2018-11-02	Listed	4.4	Standard